

## PRODUCT INFORMATION

## 60LF - 3.5 MIL CLAY COATED LAY FLAT

A 56# (92 g/m²) liner with high white visual appeal. Ideal for sheeted or fan fold applications. Designed for four-color process printing on the back side.

| Test Property                          | Units                         | Typical Value | Metric Units    | Metric Value | Test Method |
|--|-------------------------------|---------------|-----------------|--------------|-------------|
| Basis Weight                           | lbs/24X36-500<br>(3000 Sq Ft) | 56.4          | grams/sq meter  | 91.9         | TAPPI T410  |
| Caliper - Average                      | mil                           | 3.5           | um (micrometer) | 88.9         | TAPPI T411  |
| Smoothness (PPS) Liner<br>Release Side | um                            | 1.5           | um              | 1.5          | TAPPI T555  |
| Smoothness Backside                    | Sheffield Units               | 80            | Sheffield Units | 80.0         | TAPPI T538  |
| Tear-MD                                | grams                         | 67.3          | mN              | 660.0        | TAPPI T414  |
| Tear-CD                                | grams                         | 76.5          | mN              | 750.2        | TAPPI T414  |
| Tensile-MD                             | lb/inch                       | 45.7          | kN/m            | 8.0          | TAPPI T494  |
| Tensile-CD                             | lb/inch                       | 20.6          | kN/m            | 3.6          | TAPPI T494  |
| Brightness                             | %                             | 84            | %               | 84.0         | TAPPI T452  |

## **Notes**

Please see the usage guidelines in Recommendations for Storage and Handling of Layflat Label Material located in the Ink Jet/Laser section of the Product Guide.

Issued: 07/22/25

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No solespesson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions in effect at the time of the sale shall control.