

PRODUCT INFORMATION

767HM - Permanent Adhesive

A highly versatile rubber-based hot melt adhesive with quick tack. It stands up to moisture and adheres securely to both low-energy and textured surfaces.

Test Property	Units	Typical Value	Metric Units	Metric Value	Test Method
Shear (1 x 1/2 x 1 kg)	hours	14.0	hours	14.0	CPD-55
Peel - 180 D SS 20 min	lb/inch	4.5	grams/25 mm	2009.0	CPD-52
Loop Tack Stain Steel	oz/sq inch	107.1	kg/645 sq mm	3.0	CPD-16
Min. App. Temp.	F	19	С	-7	
Service Temp.	F	-65 TO 165	С	-54 TO 74	

Issued: 09/26/25

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc., products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No solesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions in effect at the time of the sale shall control.