



PRODUCT INFORMATION

057HG80361PRLF

Item #: S8939460

57# CAST COATED HI GLOSS/80361 REMOVABLE ADHESIVE/3.2 ML LAYFLAT LINER
Approximate weight per MMSI: 272 lbs. Standard core size is 6 inches. Total caliper: 7.5 mils +/- 10%

FACESTOCK

57# (85 g/m²) high-gloss sheet with a smooth, reflective surface designed for top-quality graphic reproduction.

Test Property	Units	Typical Value	Metric Units	Metric Value	Test Method
Basis Weight	lbs/25X38-500 (3300 Sq Ft)	57.4	grams/sq meter	85.0	TAPPI T410
Caliper - Average	mil	3.7	um (micrometer)	94.0	TAPPI T411
Gloss	% @ 75 degrees	90	% @ 75 degrees	90.0	TAPPI T480
Opacity	%	90	%	90.0	TAPPI T425
Smoothness (PPS) Print Side	um	.5	um	.5	TAPPI T555
Tear-MD	grams	37.7	mN	369.7	TAPPI T414
Tear-CD	grams	44.3	mN	434.4	TAPPI T414
Tensile-MD	lb/inch	37.1	kN/m	6.5	TAPPI T494
Tensile-CD	lb/inch	13.7	kN/m	2.4	TAPPI T494
Brightness	%	87.0	%	87.0	TAPPI T452

ADHESIVE

Acrylic adhesive designed for short-term removability. Consider for kiddie stickers.

Test Property	Units	Typical Value	Metric Units	Metric Value	Test Method
Caliper - Calculated	mils	0.6	um(micrometer)	15.6	
Shear (1 x 1/2 x 1 kg)	hours	2	hours	2.0	CPD-55
Peel - 180 D SS 20 min	lb/inch	1.1	grams/25 mm	491.1	CPD-52
Peel - 180 D HDPE 20 min	lb/inch	.6	grams/25 mm	267.9	CPD-52
Peel - 180 D LDPE 20 min	lb/inch	.5	grams/25 mm	223.2	CPD-52
Peel - 180 D Glass 20 min	lb/inch	1.1	grams/25 mm	491.1	CPD-52
Peel - 180 D Corrugated 20 min	lb/inch	.5	grams/25 mm	223.2	CPD-52
Loop Tack Stain Steel	oz/sq inch	32	kg/645 sq mm	.9	CPD-16
Loop Tack HDPE	oz/sq inch	25	kg/645 sq mm	.7	CPD-16
Loop Tack LDPE	oz/sq inch	18	kg/645 sq mm	.5	CPD-16
Loop Tack Corrugated	oz/sq inch	18	kg/645 sq mm	.5	CPD-16
Service Temp.	F	-50 TO 125	C	-46 TO 52	
FDA Compliance	21 CFR	175.105			

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions in effect at the time of the sale shall control.

La información presentada en esta publicación se considera correcta; no debe ser interpretada como una especificación. Los valores dados reflejan las características regulares de los materiales. Todos los informes, fichas técnicas, y recomendaciones de los productos de Green Bay Packaging Inc. están basados en pruebas que se consideran confiables, pero no constituyen ningún tipo de garantía. Todos los productos se venden con el entendimiento de que el comprador ha determinado independientemente la conveniencia de estos productos para su uso final. Ningún vendedor, representante, ni agente de Green Bay Packaging Inc. está autorizado para dar ningún tipo de garantía, ni hacer representación alguna contraria a lo susodicho.

SPECIALISTS IN COATED SELF-ADHESIVE MATERIALS

3250 South Ridge Road • P. O. Box 19017 • Green Bay, WI 54307-9017 • USA • Phone: (920)-337-1800, 800-445-4269



PRODUCT INFORMATION

LINER

A premium, 53# (87 g/m²) white kraft liner. Suitable for roll-to-sheet and fan fold applications. Designed for four-color process printing on the back side. Can be used for die cutting both paper and film.

Test Property	Units	Typical Value	Metric Units	Metric Value	Test Method
Basis Weight	lbs/24X36-500 (3000 Sq Ft)	53.4	grams/sq meter	87.0	TAPPI T410
Caliper - Average	mil	3.2	um (micrometer)	81.3	TAPPI T411
Tear-MD	grams	61.2	mN	600.2	TAPPI T414
Tear-CD	grams	66.3	mN	650.2	TAPPI T414
Tensile-MD	lb/inch	40.0	kN/m	7.0	TAPPI T494
Tensile-CD	lb/inch	18.9	kN/m	3.3	TAPPI T494

Notes

Please see the usage guidelines in Recommendations for Storage and Handling of Layflat Label Material located in the Ink Jet/Laser section of the Product Guide.

Issued: 07/03/24

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions in effect at the time of the sale shall control.

La información presentada en esta publicación se considera correcta; no debe ser interpretada como una especificación. Los valores dados reflejan las características regulares de los materiales. Todos los informes, fichas técnicas, y recomendaciones de los productos de Green Bay Packaging Inc. están basados en pruebas que se consideran confiables, pero no constituyen ningún tipo de garantía. Todos los productos se venden con el entendimiento de que el comprador ha determinado independientemente la conveniencia de estos productos para su uso final. Ningún vendedor, representante, ni agente de Green Bay Packaging Inc. está autorizado para dar ningún tipo de garantía, ni hacer representación alguna contraria a lo susodicho.