



PRODUCT INFORMATION

50HS0027541WK0758M50SC

Item #: S9158560

HI SPEED THER TRANS FSC/275 ULTRA REMOVABLE ADH/41# WHITE KRAFT LINER/758M PERMANENT ADHESIVE/3.2 SCK

Approximate weight per MMSI: 356 lbs. Standard core size is 6 inches. Total caliper: 9.9 mils +/- 10%

FACESTOCK

47# (70 g/m²) premium bright white, coated, ultra-smooth thermal transfer paper stock offering broad ribbon compatibility. FSC®-certified paper.

| Test Property | Units | Typical Value | Metric Units | Metric Value | Test Method |
|-----------------------------|-------------------------------|---------------|-----------------|--------------|-------------|
| Basis Weight | lbs/25X38-500 (3300 Sq Ft) | 47.3 | grams/sq meter | 70.0 | TAPPI T410 |
| Caliper - Average | mil | 2.9 | um (micrometer) | 73.7 | TAPPI T411 |
| Opacity | % | 88 | % | 88.0 | TAPPI T425 |
| Smoothness-Felt Side | Sheffield Units | 25 | Sheffield Units | 25.0 | TAPPI T538 |
| Smoothness (PPS) Print Side | um | 2.0 | um | 2.0 | TAPPI T555 |
| Tear-MD | grams | 42 | mN | 411.9 | TAPPI T414 |
| Tear-CD | grams | 40 | mN | 392.3 | TAPPI T414 |
| Tensile-MD | lb/inch | 26 | kN/m | 4.6 | TAPPI T494 |
| Tensile-CD | lb/inch | 17 | kN/m | 3.0 | TAPPI T494 |
| Brightness | % | 85 | % | 85.0 | TAPPI T452 |

ADHESIVE

Most universal acrylic microsphere adhering to corrugated, glass, metal, and plastics. No residue on glass or credit cards. Repositionable. Not recommended for small labels, or flood coated applications. Repulpable when applied to paper face stocks.

| Test Property | Units | Typical Value | Metric Units | Metric Value | Test Method |
|--------------------------------|------------|---------------|--------------|--------------|-------------|
| Shear (1 x 1/2 x 1 kg) | hours | .2 | hours | .2 | CPD-55 |
| Peel - 180 D SS 20 min | lb/inch | .201 | grams/25 mm | 89.7 | CPD-52 |
| Peel - 180 D Glass 20 min | lb/inch | .116 | grams/25 mm | 51.8 | CPD-52 |
| Peel - 180 D Corrugated 20 min | lb/inch | .174 | grams/25 mm | 77.7 | CPD-52 |
| Loop Tack Stain Steel | oz/sq inch | 9.73 | kg/645 sq mm | .3 | CPD-16 |
| Loop Tack HDPE | oz/sq inch | 4.0 | kg/645 sq mm | .1 | CPD-16 |
| Loop Tack LDPE | oz/sq inch | 4.7 | kg/645 sq mm | .1 | CPD-16 |
| Loop Tack Corrugated | oz/sq inch | 1.7 | kg/645 sq mm | .0 | CPD-16 |
| Loop Tack Glass | oz/sq inch | 3.0 | kg/645 sq mm | .1 | CPD-16 |
| Min. App. Temp. | F | 35 | C | 2 | |
| Service Temp. | F | 20 TO 120 | C | -7 TO 49 | |
| FDA Compliance | 21 CFR | 175.105 | | | |

Notes

Some streaking is normal with 275. Therefore, it is not recommended for small label or flood coat applications. We will honor claims if streaks are wider than 3/16 in.; or multiple smaller streaks spaced less than 3 in. apart. This adhesive is not intended for layflat applications.

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions in effect at the time of the sale shall control.

La información presentada en esta publicación se considera correcta; no debe ser interpretada como una especificación. Los valores dados reflejan las características regulares de los materiales. Todos los informes, fichas técnicas, y recomendaciones de los productos de Green Bay Packaging Inc. están basados en pruebas que se consideran confiables, pero no constituyen ningún tipo de garantía. Todos los productos se venden con el entendimiento de que el comprador ha determinado independientemente la conveniencia de estos productos para su uso final. Ningún vendedor, representante, ni agente de Green Bay Packaging Inc. está autorizado para dar ningún tipo de garantía, ni hacer representación alguna contraria a lo susodicho.



PRODUCT INFORMATION

LINER

A premium, 41# (66 g/m²) white kraft liner that is designed for roll-to-roll and fan-fold applications. Outstanding performance die cutting both paper and film.

| Test Property | Units | Typical Value | Metric Units | Metric Value | Test Method |
|-------------------|-------------------------------|---------------|-----------------|--------------|-------------|
| Basis Weight | lbs/24X36-500 (3000 Sq Ft) | 40.5 | grams/sq meter | 66.0 | TAPPI T410 |
| Caliper - Average | mil | 2.7 | um (micrometer) | 68.6 | TAPPI T411 |
| Tear-MD | grams | 46.9 | mN | 459.9 | TAPPI T414 |
| Tear-CD | grams | 54.0 | mN | 529.6 | TAPPI T414 |
| Tensile-MD | lb/inch | 32.0 | kN/m | 5.6 | TAPPI T494 |
| Tensile-CD | lb/inch | 14.3 | kN/m | 2.5 | TAPPI T494 |

ADHESIVE

An acrylic general purpose permanent adhesive with great die-cutting and stripping properties. Adheres well to many substrates, including corrugated.

| Test Property | Units | Typical Value | Metric Units | Metric Value | Test Method |
|--------------------------------|------------|---------------|--------------|--------------|-------------|
| Shear (1 x 1/2 x 1 kg) | hours | 1.3 | hours | 1.3 | CPD-55 |
| Peel - 180 D SS 20 min | lb/inch | 1.582 | grams/25 mm | 706.3 | CPD-52 |
| Peel - 180 D HDPE 20 min | lb/inch | 1.4 | grams/25 mm | 625.0 | CPD-52 |
| Peel - 180 D LDPE 20 min | lb/inch | 1.318 | grams/25 mm | 588.4 | CPD-52 |
| Peel - 180 D Glass 20 min | lb/inch | 1.676 | grams/25 mm | 748.3 | CPD-52 |
| Peel - 180 D Corrugated 20 min | lb/inch | .83 | grams/25 mm | 370.6 | CPD-52 |
| Loop Tack Stain Steel | oz/sq inch | 38 | kg/645 sq mm | 1.1 | CPD-16 |
| Loop Tack HDPE | oz/sq inch | 23 | kg/645 sq mm | .6 | CPD-16 |
| Loop Tack LDPE | oz/sq inch | 20 | kg/645 sq mm | .6 | CPD-16 |
| Loop Tack Corrugated | oz/sq inch | 14 | kg/645 sq mm | .4 | CPD-16 |
| Loop Tack Glass | oz/sq inch | 35 | kg/645 sq mm | 1.0 | CPD-16 |
| Min. App. Temp. | F | 35 | C | 2 | |
| Service Temp. | F | -65 TO 200 | C | -54 TO 93 | |
| FDA Compliance | 21 CFR | 175.105 | | | |

LINER

A white densified kraft sheet 53# (86 g/m²) with excellent point-to-point caliper control.

| Test Property | Units | Typical Value | Metric Units | Metric Value | Test Method |
|-------------------|-------------------------------|---------------|-----------------|--------------|-------------|
| Basis Weight | lbs/24X36-500 (3000 Sq Ft) | 53.5 | grams/sq meter | 87.2 | TAPPI T410 |
| Caliper - Average | mil | 3.2 | um (micrometer) | 81.3 | TAPPI T411 |
| Opacity | % | 70.0 | % | 70.0 | TAPPI T425 |
| Tear-MD | grams | 46.0 | mN | 451.1 | TAPPI T414 |
| Tear-CD | grams | 55.0 | mN | 539.4 | TAPPI T414 |
| Tensile-MD | lb/inch | 52.0 | kN/m | 9.1 | TAPPI T494 |
| Tensile-CD | lb/inch | 24.0 | kN/m | 4.2 | TAPPI T494 |
| Brightness | % | 78.0 | % | 78.0 | TAPPI T452 |

Issued: 06/14/26

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions in effect at the time of the sale shall control.

La información presentada en esta publicación se considera correcta; no debe ser interpretada como una especificación. Los valores dados reflejan las características regulares de los materiales. Todos los informes, fichas técnicas, y recomendaciones de los productos de Green Bay Packaging Inc. están basados en pruebas que se consideran confiables, pero no constituyen ningún tipo de garantía. Todos los productos se venden con el entendimiento de que el comprador ha determinado independientemente la conveniencia de estos productos para su uso final. Ningún vendedor, representante, ni agente de Green Bay Packaging Inc. está autorizado para dar ningún tipo de garantía, ni hacer representación alguna contraria a lo susodicho.