

1MBSCPP15PET6UPN102 6-Up Narrow Coupon Pattern. Roll width is 14.75"

Item #: SC510100

FACESTOCK, 0.8 mils clear BOPP.

Approximate weight per MMSI: 162 lbs. Standard core size is 3 inches. Total caliper: 3.9 mils.

Test Property	Units	Typical Value	Test Method
Yield	in²/lb.	40,800	ASTM E252
Caliper Average (Films)	mil	0.8	ASTM D374
Haze	%	2	ASTMD374
Tensile Strength at break – MD	psi	16,000	ASTM D882
Tensile Strength at break – TD	psi	38,000	ASTM D882

BREAK AWAY COATING (a non-pressure sensitive peelable adhesive).

Test Property	Units	Typical Value	Test Method
Caliper – Calculated	mils	0.4	TAPPI T411
Release Value	grams	250	Supplier

FACESTOCK, 0.8 mils clear BOPP.

Test Property	Units	Typical Value	Test Method
Yield	in²/lb.	40,800	ASTM E252
Caliper Average (Films)	mil	0.8	ASTM D374
Haze	%	2	ASTMD374
Tensile Strength at break – MD	psi	16,000	ASTM D882
Tensile Strength at break – TD	psi	38,000	ASTM D882

ADHESIVE (00102), a clear, water-resistant, film adhesive with high tack and peel. Adheres to a wide variety of surfaces.

Test Property	Units	Typical Value	Test Method
Shear 1x1/2x1 kg)	Hrs.	5.9	CPD-55
Peel 180° SS 20min	Lb./inch	1.8	CPD-52
Loop Tack SS	oz/sq inch	38	CPD-16
Min App Temp	F	40	
Service Temp	F	-40 to 160	

LINER (1.4 Mil Polyester), clear polyester liner with an excellent surface for die-cutting and high-speed automatic applications.

Test Property	Units	Typical Value	Test Method
Yield	sq in/lb.	13,968	ASTM E252
Caliper	mils	1.4	ASTM D374
Haze	%	6.5	ASTM D1003
Elongation at break – MD	%	110	ASTM D882
Elongation at break – TD	%	110	ASTM D882
Tensile – MD	Lb./sq inch	32,000	ASTM D882
Tensile – CD	Lb./sq inch	32,000	ASTM D882


Issued: 6/23/2022

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control

Notes – Shelf life of product is eight months when stored out of direct sunlight and in a cool dry area.

- Minimum Order is 3 MMSI
- Wind Liner Out, Unless Specified
- Overrun/Underrun Tolerance +/- 10%
- 5,000' or 10,000' Rolls, Shipped on the Round

Image is not to scale







The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. – Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control