

GREEN BAY PACKAGING

COATED PRODUCTS



Product Guide

Coated Products

www.gbpcoded.com

1.800.445.4269 - USA and Canada

001.920.337.1800 - Outside USA





Green Bay Packaging Inc.
COATED PRODUCTS OPERATIONS

PRESSURE-SENSITIVE LABEL STOCK STORAGE CONDITIONS AND SHELF LIFE

Storage Conditions

- The storage and converting conditions should be as close to TAPPI standards of 73°F (23°C) and 50% relative humidity as possible.
- Products should be stored in their original stretch wrap until the time they will be used on press.
- The material should be allowed to acclimate to your press room's environment for 24 hours before the stretch wrap is removed and the roll is loaded onto the press.
- Keep rolls off the concrete floors and away from any other sources of moisture contamination.
- Rotate your stock. Use the oldest inventory first.

Shelf Life

- Pressure-sensitive label material should be used within one year from date of purchase, unless otherwise stated on the data sheet.
- The one-year shelf life is part of our standard conditions of sale on all products. Green Bay Packaging will not accept any claims for pressure-sensitive material older than one year.
- The label stock should retain its functional performance after a year. The acrylic adhesive is chemically stable and will not oxidize or lose tack, and the silicone release level should remain the same.
- After application, the adhesive should not degrade or lose tack over time. However, in some applications, including very high moisture and temperature for example, adhesive performance may suffer.

LAYFLAT LABEL MATERIAL RECOMMENDATIONS

- Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60°F and 80°F (16°C and 27°C) and the relative humidity is between 40% and 60%.
- The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- Rotate your stock. Use oldest inventory first.
- Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- We are not able to guarantee layflat performance of labelstock produced with some removable adhesives.

CAN'T FIND IT ? CALL 1 - 800 - 445 - 4269



GREEN BAY PACKAGING
COATED PRODUCTS

ORDERING INFORMATION: U.S. STANDARD

MINIMUM ORDER QUANTITY
(varies by product)

INVENTORY 1 MMSI
CUSTOM 3 MMSI

TAILORED INVENTORY PROGRAM (TIP)
(delivery only within the continental USA)
SHORT LENGTH UPCHARGE

3" Minimum on all TIP Items

For items not on the Short-Length TIP program, master rolls may be cut into shorter rolls *if* the order meets the minimum quantity of 1 MMSI for inventoried products or up to 3 MMSI for custom runs.

Roll Length	Charge
1,250' to 2,499'	\$.05/MSI
500' to 1,249'	\$.10/MSI
150' to 499'	\$.15/MSI

CUSTOM REWINDING/SPLICING UPCHARGE

.03/MSI

SLITTING UPCHARGE

0-17 cuts, no upcharge
18+ cuts .02/MSI
2" minimum slit width

SLITTING TOLERANCE

+/- 1/32"

CORE SIZES

For core size, see the Data Sheet for your specific item.

OVERRUN / UNDERRUN FINISHING ALLOWANCES

TIP	+/- 5%
Inventory	+/- 5%
Custom Single Pass	+/- 10%
Piggybacks	+/- 15%
Special Materials	+/- 20%

Product shelf life is one year unless otherwise stated on the component data sheet.

In addition to +/- % on overall order quantity, roll length may also be +/- % of ordered length. Customers may designate "exact roll length" on non-trimless items only. Additional splices may be required to meet exact roll length requests.

CAN'T FIND IT ? CALL 1 - 800 - 445 - 4269



GREEN BAY PACKAGING
COATED PRODUCTS

ORDERING INFORMATION: METRIC SYSTEM

MINIMUM ORDER QUANTITY

(varies by product)

TAILORED INVENTORY PROGRAM (TIP)

(delivery only within the continental USA)

SHORT LENGTH UPCHARGE

**INVENTORY
CUSTOM**

645 sq. Mts

1935 sq. Mts

76.2mm Minimum on all TIP Items

For items not on the Short-Length TIP program, master rolls may be cut into shorter rolls *if* the order meets the minimum quantity of 1 MMSI for inventoried products or up to 3 MMSI for custom runs.

<u>Roll Length</u>	<u>Charge</u>
380 to 761 Meters	\$.05/MSI
152 to 379 Meters	\$.10/MSI
45.7 to 151 Meters	\$.15/MSI

**CUSTOM REWINDING/SPLICING
UPCHARGE**

.05/sq. Mts

SLITTING UPCHARGE

0-17 cuts, no upcharge
18+ cuts .03/sq. Mts
51mm minimum slit width

SLITTING TOLERANCE

+/- 0.7mm

CORE SIZES

For core size, see the Data Sheet for your specific item.

**OVERRUN / UNDERRUN
FINISHING ALLOWANCES**

Inventory	+/- 5%
Custom Single Pass	+/- 10%
Piggybacks	+/- 15%
Special Materials	+/- 20%

Product shelf life is one year unless otherwise stated on the component data sheet.

In addition to +/- % on overall order quantity, roll length may also be +/- % of ordered length. Customers may designate "exact roll length" on non-trimless items only. Additional splices may be required to meet exact roll length requests.

CAN'T FIND IT ? CALL 1 - 800 - 445 - 4269

TERMS AND CONDITIONS

- Entire Agreement.** These Terms and Conditions shall constitute the entire agreement (the "Agreement" or "Terms and Conditions") of Green Bay Packaging Inc. ("Seller") and Buyer with respect to the subject matter hereof. These Terms and Conditions are controlling and shall supersede any prior or contemporaneous agreements, understandings or representations, oral or written, relating to the subject matter hereof. These Terms and Conditions shall govern in the event of any conflict between these Terms and Conditions and any provision contained in any subsequent Purchase Order or otherwise, the terms of which, whether conflicting, supplemental or otherwise, are hereby expressly rejected.
- Shipment, Title and Risk of Loss.** Unless otherwise mutually agreed in writing, shipment shall be F.O.B. Origin. Title and risk of loss pass from Seller to Buyer upon delivery to a carrier.
- Freight.** Shipments are F.O.B. Origin, with full freight allowed on shipments of 9 MMSI or more. Inventory and non-inventory items may be combined to meet the 9 MMSI minimum requirement for full freight allowed shipments, provided entire order is shipped at one time from one location to one destination. For all shipments fewer than 9 MMSI terms are F.O.B. Origin, freight prepaid and added, in which the shipping and handling charges shall be added to the face amount of the invoice.
- Payment.** Net 30 days following the date of invoice. 1% discount on payments received within 10 days of date of invoice. Amounts not paid in full within 30 days of date of invoice will be subject to a service charge of 1% per month on the unpaid balance to be included on each month's statement until paid in full.
- Taxes and Other Charges.** In addition to any price herein provided, Buyer shall be liable for any tax, fee or other charge imposed on Seller at any time upon the sale and/or shipment of the goods sold hereunder, now imposed by federal, state, municipal or any other governmental authorities or hereafter becoming effective for or during the period hereof.
- Cancellation or Default by Buyer.** This order may not be cancelled in whole or in part by Buyer except with Seller's written consent. If at any time, in Seller's opinion, Buyer's credit is impaired, or if Buyer shall fail to pay to Seller any amount when due, under this Agreement or any other agreement, or if at any time Buyer shall indicate an intention to refuse to perform or on an inability to perform its obligation hereunder, Seller may at its option terminate this Agreement as regards further shipments and thereupon all obligations of Buyer with respect to shipments previously made shall become immediately due and payable. In the event of such termination, Buyer shall remain liable to Seller for any and all loss or damage sustained due to Buyer's default.
- Force Majeure.** Seller shall not be liable for any loss, damage, delays, changes in shipment schedules or failure to deliver caused by any event beyond its reasonable control, including, without limitation, accident, fire, actual or threatened strike or riot, explosion, mechanical breakdown (including technological or information systems), plant shutdown, unavailability of or interference with necessary transportation, any raw material or power shortage, compliance with any law, regulation or order, acts of God or public enemy, prior orders from others, or limitations on Seller's or its suppliers' products or marketing activities or any other cause or contingency beyond Seller's control. If by reason of any such circumstance, Seller's supply of the goods herein specified shall be insufficient to meet all requirements, including its own, Seller shall have the right, at its option and without liability, to allocate its available supply of goods among its present and future customers, including Seller's affiliated divisions and companies, in such manner as Seller deems equitable.
- Limitation on Warranty and Remedies.** Seller warrants that the goods to be sold hereunder will conform to the description on the face hereof, and any specifications provided in writing to Buyer and will be of Seller's standard quality. Buyer represents that it has used its own independent skill and expertise in connection with the selection and use of the goods purchased pursuant to this Agreement, and that it will independently determine the suitability for each use for which it is purchased. When UL recognition is provided to Buyer, goods will meet applicable guidelines of Underwriting Laboratories. **THIS WARRANTY IS EXCLUSIVE, AND EXCEPT AS EXPRESSLY SET OUT IN THIS AGREEMENT, SELLER MAKES NO OTHER WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, AND DISCLAIMS ALL OTHER WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN THE EVENT THE GOODS ARE NOT IN COMPLIANCE WITH SELLER'S WARRANTY HEREUNDER, BUYER'S SOLE REMEDY SHALL BE A CREDIT FOR THE COST OF SUCH GOODS OR, AT SELLER'S OPTION, REPLACEMENT OF SUCH GOODS. SELLER SHALL UNDER NO CIRCUMSTANCES, WHETHER FOR A FAILURE OF ITS LIMITED REMEDY OR OTHERWISE, BE LIABLE TO BUYER OR OTHERWISE FOR SPECIAL, INCIDENTAL, DIRECT, PUNITIVE, OR CONSEQUENTIAL DAMAGES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN OFFICER OF SELLER. All warranties and certifications are made by Seller to Buyer and to no other parties including, but not limited to, Buyer's customers and any other end users.**
- Limitation of Actions.** Any claim must be made in writing within 10 days after receipt of goods, if for quantity, or within 30 days after receipt of goods, if for quality, loss of or damage to goods, and the goods must be held available at Buyer's place of business for Seller's inspection. Any action for breach of this Agreement, other than for non-payment hereunder, must be commenced within one year of the date of shipment, or due date of delivery in the event of non-delivery, of the particular shipment upon which such claim is based. No claim may in any event be made after goods have in any way been used or processed by the Buyer. Buyer's remedies set forth herein are exclusive and the total liability of Seller for damages with respect to this Agreement, or anything done in connection therewith, shall be limited to the purchase price of the particular shipment with respect to which such damages are claimed.
- Returns and Transit Damage Claims.** No goods may be returned to Seller without Seller's written consent. Goods returned without Seller's prior written authorization will be refused. Buyer must note any shortage or damage on the delivery receipt at the time of delivery. Any concealed damage must be reported to the delivering carrier within 5 days, and the entire package must be retained at Buyer's place of business until after a damage inspection report is issued by the carrier. The following documents must accompany any transit damage claim: original paid freight bill; original or certified copy of the original bill of lading; copy of the invoice for the shipment; copy of the destination inspection report or delivery receipt noting the shortage or damage.
- Governing Law.** This Agreement shall be governed by and construed in accordance with the internal laws of the state of Wisconsin, U.S.A.
- Amendment.** This Agreement shall not be amended except by a writing signed by an officer of the Seller and specifically stating that it is an amendment.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
WHITE PAPERS - HIGH-GLOSS			
57# CAST COATED HIGH-GLOSS	057HG	57# (85 g/m ²) high-gloss sheet with a smooth, reflective surface designed for top-quality graphic reproduction.	3.7 95.0
ENCORE GLOSS	060EG	61# (89 g/m ²) super calendered high-gloss sheet. This C1S paper is designed for premium labeling applications. Non-cast coated paper featuring excellent gloss and suitable for process printing.	2.8 72.0
WHITE PAPERS - SEMI-GLOSS			
53# SEMI-GLOSS OPAQUE	054SA	53# (78 g/m ²) semi-gloss with a gray opaque barrier coating on the back. Designed for cover up labels. Excellent opacity, so the errors will not be visible. Smooth print surface for attractive graphic reproduction. FSC®-certified paper.	2.6 66.0
53# SEMI-GLOSS	054SG	53# (78 g/m ²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, toner, and offset methods. FSC®-certified paper.	2.6 66.0
54# WET STRENGTH SEMI-GLOSS	054WS	54# (80 g/m ²) C1S blue-white semi-gloss. Wet strength stands up to moisture. Ideal for chilled beverages, including beer and wine, or refrigerated foods. Smooth surface enhances print results with flexo, laser and other press types. FSC®-certified paper.	2.9 80.0
SEMI-GLOSS PREFERRED OPAQUE	060PA	60# (88.8/m ²) Semi-Gloss Preferred (060PR) with a gray opaque barrier coating. Designed for cover up labels. Excellent print surface with flexo, toner, or offset. FSC®-certified paper.	3.1 79.0
SEMI-GLOSS PREFERRED	060PR	60# (88.8/m ²) semi-gloss, multi-purpose paper with superior gloss and print qualities. A warm white color. Excellent print surface for flexo, toner, or offset. FSC®-certified paper.	3.1 79.0
58# SEMI-GLOSS	060SG	58# (87 g/m ²) semi-gloss multi-purpose paper with superior gloss and print qualities. Bright blue-white shade. Excellent graphic results with flexo, offset, or toner-based printing. FSC®-certified paper.	3.0 76.0
80# SEMI-GLOSS	080SG	80# (118 g/m ²) semi-gloss multi-purpose paper with superior gloss and print qualities. Bright blue-white shade. Excellent print surface for flexo, toner, or offset. This heavier sheet offers greater stiffness and opacity. FSC®-certified paper.	4.2 107.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
WHITE PAPERS - SEMI-GLOSS (cont.)			
55# SEMI-GLOSS	55SSG	55# (78 g/m ²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, toner, and offset methods. FSC®-certified paper.	2.9 73.7
FSC® CERTIFIED 53# SEMI-GLOSS PAPER	F54SG	53# (78 g/m ²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, toner, and offset methods. FSC®-certified paper.	2.9 74.0
60# SEMI-GLOSS WITH 30% POST-CONSUMER WASTE	R60SG	A 60# (89 g/m ²) semi-gloss face stock with 30% post-consumer recycled fiber. Excellent strength characteristics enhance label converting and application. Smooth print surface for outstanding graphics. FSC®-certified paper.	2.7 68.6

WHITE PAPERS - MATTE

60# LITHO MATTE	060LM	A 60# (89 g/m ²) clay-coated matte smooth paper. Offers a great printing surface for excellent graphic reproduction. Its very matte appearance provides a unique look in package design. Perfect for flexo printing and in a variety of digital presses.	3.8 97.0
60# DULL LITHO	061DL	60# (89 g/m ²) high quality, dull finish litho offering excellent print and die-cut properties. Good for flexographic and offset printing. FSC®-certified paper.	3.0 76.0

WHITE PAPERS - INDIGO TOPCOATED

INDIGO TOPCOATED 55# SEMI-GLOSS	D55SG	55# (81 g/m ²) semi-gloss sheet designed for printing on HP Indigo presses. It has been certified by RIT for use on the ws4500 and ws6000 presses. Has a blue-white shade with high brightness and opacity. Exceptionally strong. FSC®-certified paper.	3.0 76.0
--	--------------	---	-------------

TAG STOCK

8 POINT GLOSS WHITE CLAY COATED TAG	008GB	A glossy, bright white, 130# (192 g/m ²) board with excellent print characteristics. Coated on both sides, allowing for multiple uses - as a tag, or in a pressure-sensitive structure. FSC®-certified paper.	8.0 203.0
--	--------------	---	--------------



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
EDP			
50# EDP SMUDGE RESISTANT	050ED	A 50# (74 g/m ²) general purpose uncoated paper. Bright white with excellent smudge resistance. Designed for high performance. FSC®-certified paper.	3.5 88.9
PHARMACEUTICAL			
DIRECT THERMAL PRESCRIPTION VIAL LABEL	021RX	This 48# (71 g/m ²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.	3.1 78.0
40# PHARMACEUTICAL LITHO	040PL	40# (60 g/m ²) lightweight C1S semi-gloss litho with good ink holdout. Candidate for pharmaceutical and nutritional labeling.	2.0 52.0
DIRECT THERMAL PRESCRIPTION VIAL LABEL	20RXE	This 48# (71 g/m ²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.	3.0 76.2
FLUORESCENT PAPERS			
BLUE FLUORESCENT	054BZ	57# (84 g/m ²) blue matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. Unique color makes labels stand out. Offers another option when using color coded labels. FSC®-certified paper.	3.9 99.0
GREEN FLUORESCENT	054GZ	57# (84 g/m ²) green matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.	3.9 99.0
ORANGE FLUORESCENT	054OZ	57# (84 g/m ²) orange matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.	3.9 99.0
PINK FLUORESCENT	054PZ	57# (84 g/m ²) pink matte fluorescent coated paper. Designed for laser, price marking, inkjet, promotional and general roll label applications. FSC®-certified paper.	3.9 99.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
FLUORESCENT PAPERS (cont.)			
RED FLUORESCENT	054RZ	57# (84 g/m ²) red matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.	3.9 99.0
YELLOW CHARTREUSE FLUORESCENT	054YZ	57# (84 g/m ²) yellow chartreuse matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.	3.9 99.0
BEER & WINE LABEL			
54# WET STRENGTH SEMI-GLOSS	054WS	54# (80 g/m ²) C1S blue-white semi-gloss. Wet strength stands up to moisture. Ideal for chilled beverages, including beer and wine, or refrigerated foods. Smooth surface enhances print results with flexo, laser and other press types. FSC®-certified paper.	2.9 80.0
CLASSIC CREST* SOLAR WHITE SMOOTH	0WCSW	60# (89 g/m ²) smooth, uncoated white paper with an excellent printing surface, high strength, and dimensional stability. Perfect for wine labels and other upscale products. FSC®-certified paper. *Registered Trademark of Neenah Paper, Inc.	4.4 112.0
ESTATE LABEL* #4 WHITE LAID	0WEL4	60# (89 g/m ²) white, laid, uncoated, wet strength paper. Maintains its visual integrity when wet. Perfect for wine and beer labels. Its high-end look matches well with upscale products. *Registered Trademark of Neenah Paper, Inc. FSC®-certified paper.	5.5 140.0
ESTATE LABEL* #8 WHITE SMOOTH	0WEL8	60# (89 g/m ²) uncoated, white, wet strength paper. Maintains its integrity when wet. Designed for wine and other high-end labels, such as gourmet foods and cosmetics. *Registered Trademark of Neenah Paper, Inc. FSC®-certified paper.	4.8 122.0
ESTATE LABEL* #9 CREAM LAID	0WEL9	60# (89 g/m ²) uncoated cream wet strength paper. Maintains its integrity when wet. Perfect for wine and other upscale labels, such as gourmet foods and cosmetics. FSC®-certified paper. *Registered Trademark of Neenah Paper, Inc.	5.4 137.0
SILVER METALIZED WET STRENGTH PAPER	56MSW	56# (83 g/m ²) top coated silver metalized paper. Wet strength for use in moist environments including refrigerated foods and chilled beverages. The metallic look makes a product's graphics stand out. Not recommended for HP Indigo Presses.	2.8 71.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
BEER & WINE LABEL (cont.)			
70# BRIGHT WHITE FELT	70BWF	70# (103 g/m ²) uncoated bright white, wet strength paper. Perfect for wine, beer, and other beverage labels. The rich weight and texture makes it ideal for upscale food, home, and personal care products. FSC®-certified paper.	5.7 145.0
60# BLACK VELLUM	BKVLM	60# (89 g/m ²) uncoated, black, smooth, wet strength paper. Maintains its integrity when wet. While it was designed for wine, beer, and other beverage labels, its unique look will make any product stand out on store shelves. FSC®-certified paper.	4.8 122.0
50# KONA LIGHT ROAST	KONAL	KONAL is a 50# (74g/m ²), 100% PCW recycled wet strength product. A blend of repurposed coffee bean bag fiber and post-consumer waste material. Perfect for labeling any coffee-related product, or environmentally-friendly packaging. FSC®-certified paper.	4.1 104.0
60# 100% PCW WET STRENGTH PAPER	PLRNB	A 60# (89 g/m ²) FSC®-certified, 100% post-consumer waste paper with wet strength. Resistant to moisture, it's perfect for beverage applications, like wine, beer and chilled spirits. Its luxurious look will enhance upscale food and personal care products.	4.3 109.0

SPECIALTY PAPERS

54# WET STRENGTH SEMI-GLOSS	054WS	54# (80 g/m ²) C1S blue-white semi-gloss. Wet strength stands up to moisture. Ideal for chilled beverages, including beer and wine, or refrigerated foods. Smooth surface enhances print results with flexo, laser and other press types. FSC®-certified paper.	2.9 80.0
BROWN NATURAL KRAFT	060GM	60# (89 g/m ²) brown natural kraft paper. The natural look makes it perfect for labeling organic or other earth-friendly products. It can also be used for cover-up labels on corrugated containers.	5.5 140.0
TRANSLUCENT PAPER	1TRCT	A 42# (62 g/m ²) ultra-clear translucent paper. It is well-suited for wafer seal mailing tabs. Can be used for tamper-evident seals. Also provides a unique look for primary package decoration.	2.3 58.4
TRANSLUCENT PAPER	3TRCT	A 33# (49 g/m ²) ultra-clear translucent paper. It is well-suited for wafer seal mailing tabs. Can be used for tamper-evident seals. Also provides a unique look for primary package decoration.	2.2 55.9



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
SPECIALTY PAPERS (cont.)			
DISSOLVABLE PAPER	H2ODP	A water-soluble paper. Coated with the dissolvable adhesive, 611, it disappears in seconds under running water. Leaves no residue on the container. Best dissolvable performance when printed with water-based inks. Keep wrapped until used. FSC®-certified.	3.5 89.0
50# KONA LIGHT ROAST	KONAL	KONAL is a 50# (74g/m ²), 100% PCW recycled wet strength product. A blend of repurposed coffee bean bag fiber and post-consumer waste material. Perfect for labeling any coffee-related product, or environmentally-friendly packaging. FSC®-certified paper.	4.1 104.0
LAMINATED FOILS			
BRIGHT GOLD FOIL	055BG	Top coated 70# (104 g/m ²) bright gold laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.	3.6 91.0
BRIGHT SILVER FOIL	055BS	Top coated 70# (104 g/m ²) bright silver laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.	3.6 91.0
DULL GOLD FOIL	055DG	Top coated 70# (104 g/m ²) dull gold laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.	3.6 91.0
DULL SILVER FOIL	055DS	Top coated 70# (104 g/m ²) dull silver laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.	3.6 91.0
FOIL SUBSTITUTES			
1.85 MIL SILVER METALIZED BOPP	018MT	1.85 mil clear BOPP metalized on the back for durability. Top coated for print compatibility with water-based and UV flexo, and UV inkjet. Great stiffness for automatic application. Ideal for bright label graphics that will catch the eye of the consumer.	1.9 47.0
2.0 MIL SILVER METALIZED BOPP	021MU	A 2.0 mil BOPP metalized on the back side for a shiny silver appearance. Top coated for printability with a wide range of ink systems.	2.0 51.0
HOLOGRAM PRISMATIC DIFFRACTION: RAINBOW	056H5	64# (94 g/m ²) decorative prismatic diffraction paper. Shim lines/seams are present in holographic material. This gap in the pattern will be up to 1/32" wide. The area between the shim lines measures 30" machine direction (MD) and 48" cross direction (CD).	3.3 84.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
FOIL SUBSTITUTES (cont.)			
56# SILVER METALIZED PAPER	057MS	56# (83 g/m ²) top coated silver metalized paper. Not recommended for HP Indigo Presses.	2.5 64.0
SILVER METALIZED WET STRENGTH PAPER	56MSW	56# (83 g/m ²) top coated silver metalized paper. Wet strength for use in moist environments including refrigerated foods and chilled beverages. The metallic look makes a product's graphics stand out. Not recommended for HP Indigo Presses.	2.8 71.0
THERMAL TRANSFER			
2.6 MIL THERMAL TRANSFER WHITE LABEL-LYTE™	026TT	2.6 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is required. Label-Lyte is a trademark of Jindal Films America.	2.6 66.0
THERMAL TRANSFER WHITE LABEL-LYTE™	030TT	3.0 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is important. Label-Lyte is a Trademark of Jindal Films America.	3.0 76.0
HIGH SPEED COATED THERMAL TRANSFER	050HS	47# (70 g/m ²) premium bright white, coated, ultra-smooth thermal transfer paper stock offering broad ribbon compatibility. FSC®-certified paper.	3.0 76.0
3.0 MIL TC MATTE WHITE BOPP	075WP	A 3.0 mil top coated matte white BOPP. A synthetic paper, it can be used with thermal transfer, flexography, screen, letterpress, and other print methods. It is moisture, chemical and tear resistant.	3.0 75.0
TOP COATED KIMDURA® FPG 95	095TK	A 4.2 mil Kimdura® BOPP specially top coated for thermal transfer, dot matrix, ion deposition and digital printing. Registered Trademark of Neenah Paper, Inc. © 2007 NPI All Rights Reserved.	4.2 107.0
SELECT THERMAL TRANSFER OPAQUE	0TTFA	A 44# (65 g/m ²) gray opaque multi-purpose thermal transfer sheet. Designed for cover up labels, with excellent opacity. Premium coating for enhanced flexo graphics. FSC®-certified paper.	2.9 72.0
SELECT THERMAL TRANSFER	0TTFP	A 44# (65 g/m ²) multi-purpose thermal transfer sheet. Premium coating for enhanced flexo-printed graphics. FSC®-certified paper.	2.9 72.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
THERMAL TRANSFER (cont.)			
MATTE WHITE BOPP	100WP	A 3.7 mil top coated matte white BOPP. UV resistant. A synthetic paper, it can be printed by thermal transfer, flexography, screen, and letterpress. Moisture, chemical and tear resistant. For drum label, outdoor and other demanding applications.	3.7 95.0
VALUE THERMAL TRANSFER	VALTE	A 42# (62 g/m ²), top-coated thermal transfer sheet that offers high performance at a lower cost. Strength and opacity are comparable to conventional thermal transfer facers. Exceptional print quality, especially for flood coating. FSC®-certified paper.	2.4 61.0
VALUE THERMAL TRANSFER	VALUT	A 42# (62 g/m ²) top-coated, thermal transfer sheet that offers high performance at a lower cost. Strength and opacity are comparable to conventional thermal transfer facers. Exceptional print quality, especially for flood coating. FSC®-certified paper.	2.8 71.0
DIRECT THERMAL			
PREMIUM TOP COATED DT	24VTE	A 50# (74 g/m ²) top coated no phenols added paper. Resists moisture, heat, humidity, fading, scuffing, chemicals, and plasticizers. Use for weigh scale applications, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper.	3.0 76.2
3.3 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	84MBE	A 3.3 mil BOPP, no phenols added film, with direct thermal coating. Top coated for durability. Medium degree of sensitivity. Use when moisture and environmental resistance are important. Good stiffness for ease of dispensing. Dark image for excellent ability to be read and scanned.	3.3 83.8
2.9 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	70MKE	A 2.9 mil BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	2.9 73.7
TOP COATED DIRECT THERMAL PAPER	015DT	A 38# (56.2 g/m ²) high sensitivity, top coated direct thermal paper. This thinner caliper facer allows more labels per roll. Ideal for hand-applied mobile printing applications. FSC®-certified paper.	2.3 58.4
DIRECT THERMAL PRESCRIPTION VIAL LABEL	20RXE	This 48# (71 g/m ²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.	3.0 76.2



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
DIRECT THERMAL (cont.)			
DIRECT THERMAL PRESCRIPTION VIAL LABEL	021RX	This 48# (71 g/m ²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.	3.1 78.0
RED FLUORESCENT DIRECT THERMAL	022FT	A 54# (80 g/m ²) bright red direct thermal coated paper. Images black. Intended for attention-grabbing promotional point-of-purchase labels, or color coded warehouse tracking. FSC®-certified paper.	3.1 79.0
PREMIUM TOP COATED TD	022TD	A 53# (78 g/m ²) top coated direct thermal coated paper for more demanding applications and higher imaging speeds. FSC®-certified paper.	3.1 79.0
PREMIUM TOP COATED DT	22TDE	A 51# (74 g/m ²), no phenols added, top coated direct thermal paper ideal for more demanding applications and higher imaging speeds. FSC®-certified paper.	3.2 74.0
NEAR IR PACKAGE DELIVERY DIRECT THERMAL	22PDE	A 48# (70 g/m ²), no phenols added, direct thermal paper top-coated for handling durability. Near IR designed for package delivery. PCS and scanning up to 670 nm. For high-heat environments. Resists imaging up to 100°C. Moderate to fast print speeds. FSC®-certified paper.	3.1 78.7
ECONOMY TOP COATED DIRECT THERMAL PAPER	23DTE	A 48# (72 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, alcohol and heat. Ideal for shipping and warehousing applications. FSC®-certified paper.	3.0 76.2
ECONOMY TOP COATED DIRECT THERMAL PAPER	024DT	A 53# (78 g/m ²) top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.	3.2 81.0
ECONOMY TOP COATED DIRECT THERMAL PAPER	24DTE	A 50# (74 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.	2.9 73.7
NON-TOP COATED DIRECT THERMAL PAPER	024NT	A 47# (69.9 g/m ²) medium sensitivity non-top coated direct thermal paper designed for short duration labels or applications where the label is not exposed to solvents, water, oils, fats or other similar materials. FSC®-certified paper.	3.1 78.7



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
DIRECT THERMAL (cont.)			
ECONOMY TOP COATED DIRECT THERMAL PAPER	025DT	A 47# (70 g/m ²) top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.	3.1 79.0
ECONOMY TOP COATED DIRECT THERMAL PAPER	25DTE	A 49# (72.5 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.	3.0 76.2
NON-TOP COATED DIRECT THERMAL PAPER	025NT	A 51# (75 g/m ²) medium sensitivity non-top coated direct thermal paper designed for short duration labels or applications where the label is not exposed to solvents, water, oils, fats or other similar materials. FSC®-certified paper.	3.3 82.5
NON-TOP COATED DIRECT THERMAL PAPER	25NTE	A 49# (73 g/m ²), no phenols added, medium sensitivity non-top coated direct thermal paper designed for short duration labels or applications where the label is not exposed to solvents, water, oils, fats or other similar materials. FSC®-certified paper.	3.2 81.3
3.0 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	070MK	A 3.0 mil BOPP direct thermal film. Medium degree of sensitivity. Top coated for durability. Use when moisture and environmental resistance are important. Dark image for excellent ability to be read and scanned.	3.0 76.0
3.3 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	084MB	A 3.3 mil BOPP direct thermal film. Top coated for durability. Medium degree of sensitivity. Use when moisture and environmental resistance are important. Good stiffness for ease of dispensing. Dark image for excellent ability to be read and scanned.	3.3 84.0
SYNTHETIC MEDIUM SENSITIVITY FILM	095RK	4.1 mil white BOPP film with direct thermal coating. Top coated for durability. Medium degree of sensitivity.	4.1 104.0
SYNTHETIC MEDIUM SENSITIVITY FILM	096RK	4.1 mil white BOPP film with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	4.1 104.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
DIRECT THERMAL (cont.)			
SYNTHETIC MEDIUM SENSITIVITY FILM	96RKE	4.0 mil white BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	4.0 101.6
TOP-COATED VALUE DIRECT THERMAL OPAQUE	24VTA	A 48# (71 g/m ²) top coated direct thermal paper with a gray opaque backside coating. Designed for cover up labels. Good environmental resistance for weigh scale, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper.	3.2 80.0
TOP COATED VALUE DIRECT THERMAL	24VTB	A 48# (71 g/m ²) top coated paper. Resists moisture, heat, humidity, fading, scuffing, chemicals, and plasticizers. Use for weigh scale applications, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper.	3.2 80.0
3.0 MIL CLEAR DIRECT THERMAL FILM	30CDT	A 3.0 mil top-coated direct thermal polypropylene film with exceptional clarity. Designed for variable image printed labels that highlight the product. Has environmental and water resistance. White should be printed behind any barcode for scannability.	3.0 76.0

DIRECT THERMAL (NO PHENOLS ADDED)

PREMIUM TOP COATED DT	24VTE	A 50# (74 g/m ²) top coated no phenols added paper. Resists moisture, heat, humidity, fading, scuffing, chemicals, and plasticizers. Use for weigh scale applications, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper.	3.0 76.2
3.3 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	84MBE	A 3.3 mil BOPP, no phenols added film, with direct thermal coating. Top coated for durability. Medium degree of sensitivity. Use when moisture and environmental resistance are important. Good stiffness for ease of dispensing. Dark image for excellent ability to be read and scanned.	3.3 83.8
2.9 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	70MKE	A 2.9 mil BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	2.9 73.7



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
DIRECT THERMAL (NO PHENOLS ADDED) (cont.)			
DIRECT THERMAL PRESCRIPTION VIAL LABEL	20RXE	This 48# (71 g/m ²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.	3.0 76.2
DIRECT THERMAL PRESCRIPTION VIAL LABEL	021RX	This 48# (71 g/m ²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.	3.1 78.0
NEAR IR PACKAGE DELIVERY DIRECT THERMAL	22PDE	A 48# (70 g/m ²), no phenols added, direct thermal paper top-coated for handling durability. Near IR designed for package delivery. PCS and scanning up to 670 nm. For high-heat environments. Resists imaging up to 100°C. Moderate to fast print speeds. FSC®-certified paper.	3.1 78.7
PREMIUM TOP COATED DT	22TDE	A 51# (74 g/m ²), no phenols added, top coated direct thermal paper ideal for more demanding applications and higher imaging speeds. FSC®-certified paper.	3.2 74.0
ECONOMY TOP COATED DIRECT THERMAL PAPER	23DTE	A 48# (72 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, alcohol and heat. Ideal for shipping and warehousing applications. FSC®-certified paper.	3.0 76.2
ECONOMY TOP COATED DIRECT THERMAL PAPER	24DTE	A 50# (74 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.	2.9 73.7
ECONOMY TOP COATED DIRECT THERMAL PAPER	25DTE	A 49# (72.5 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.	3.0 76.2
NON-TOP COATED DIRECT THERMAL PAPER	25NTE	A 49# (73 g/m ²), no phenols added, medium sensitivity non-top coated direct thermal paper designed for short duration labels or applications where the label is not exposed to solvents, water, oils, fats or other similar materials. FSC®-certified paper.	3.2 81.3



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
DIRECT THERMAL (NO PHENOLS ADDED) (cont.)			
SYNTHETIC MEDIUM SENSITIVITY FILM	96RKE	4.0 mil white BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	4.0 101.6
INK JET / LASER			
50# LASER JET WITH 100% PCW	R51LJ	A 50# (74 g/m ²) multi-purpose facer for laser and inkjet printing. Produced with 100% post-consumer waste. Has a bright, white color, so it is attractive while helping the environment. FSC® certified.	4.0 101.6
SUPER BRIGHT LASER JET	050LJ	51# (75 g/m ²) Exceptionally bright, uncoated, multi-purpose sheet for both laser and ink jet printing. FSC®-certified paper.	4.0 102.0
BLUE FLUORESCENT	054BZ	57# (84 g/m ²) blue matte fluorescent coated paper. Designed for laser, price marking, promotional and general roll label applications. Unique color makes labels stand out. Offers another option when using color coded labels. FSC®-certified paper.	3.9 99.0
GREEN FLUORESCENT	054GZ	57# (84 g/m ²) green matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.	3.9 99.0
ORANGE FLUORESCENT	054OZ	57# (84 g/m ²) orange matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.	3.9 99.0
PINK FLUORESCENT	054PZ	57# (84 g/m ²) pink matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.	3.9 99.0
RED FLUORESCENT	054RZ	57# (84 g/m ²) red matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.	3.9 99.0
YELLOW CHARTREUSE FLUORESCENT	054YZ	57# (84 g/m ²) yellow chartreuse matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.	3.9 99.0
60# MATTE-COATED INK JET	07INK	A 60# (88 g/m ²) matte-coated, acid-free, inkjet sheet with an exceptionally bright, blue-white shade. It provides high resolution imaging, and excellent smear and water resistance. It is compatible with a broad array of inkjet printers. FSC®-certified.	4.5 114.3



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
INK JET / LASER (cont.)			
59# GLOSS INKJET PAPER	1GINK	A 59# (87 g/m ²) high gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. Not recommended for flexo printing. FSC®-certified.	4.1 104.0
55# SEMI-GLOSS INKJET PAPER	SGINK	A 55# (81.4 g/m ²) semi gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks.	3.4 86.4
65# SEMI-GLOSS INKJET PAPER	SG2NK	A 65# (97 g/m ²) semi gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. FSC®-certified.	4.5 114.3
3.4 MIL MATTE WHITE INK JET BOPP	34WIJ	A 3.4 mil white matte BOPP that is a multi-purpose film for both water-based and pigment ink jet printing. Quick drying on press. The smooth surface allows graphics to really stand out on both black and white, and color printers. Good moisture resistance.	3.4 86.0
47# FSC®-CERTIFIED SUPER BRIGHT LASER JET	F47LJ	47# (70 g/m ²) Exceptionally bright, uncoated, multi-purpose sheet for laser and ink jet printing. Lighter weight for shipping savings. Thinner caliper for space savings and reduced packaging. Offers the option of more labels on a roll. FSC®-certified.	3.5 89.0

FILMS: POLYPROPYLENES (CLEAR)

1.85 MIL CLEAR TOP COATED BOPP	018CT	1.85 mil clear top-coated BOPP is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Ultra clear for a no-label look. Perfect for health and beauty aid, household care, and beverage labeling.	1.9 47.0
2.0 MIL CLEAR TOP COATED BOPP	020CL	2.0 mil clear top-coated BOPP offers excellent print results with water-based and UV flexo ink systems, and hot stamping. Ultra clear for a no-label look. Perfect for health and beauty aid, household care, pharmaceutical, and beverage labeling.	2.0 51.0
2.2 MIL FLEXICLEAR™ TC CONFORMABLE BOPP	022FC	A 2.2 mil top coated clear BOPP offering full wall-to-wall squeeze conformability. Glossy look with a superior print receptive top coating for excellent ink adhesion and print quality. FlexiClear™ is a Trademark of Green Bay Packaging Inc.	2.2 56.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
FILMS: POLYPROPYLENES (CLEAR) (cont.)			
3.6 MIL CLEAR TC BOPP	036CG	A 3.6 mil clear BOPP film. UV resistance and top coating suitable for UV screen, UV flexo and waterbased inks. Can be used for window graphics, or other applications where a more substantial film is needed.	3.6 91.0
FILMS: POLYPROPYLENES (WHITE)			
2.2 MIL FLEXIWHITE™ TC CONFORMABLE BOPP	022FW	A 2.2 mil top coated white BOPP offering full wall-to-wall squeeze conformability. Glossy look with a superior print receptive top coating for excellent ink adhesion and print quality. FlexiWhite™ is a Trademark of Green Bay Packaging Inc.	2.2 56.0
2.3 MIL TOP COATED WHITE BOPP	023WB	A 2.3 mil white top coated BOPP, backside coated to aid in adhesive anchorage. Excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.	2.3 58.0
2.3 MIL WHITE TOP COATED BOPP	023WP	A 2.3 mil white top coated BOPP with excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.	2.3 58.0
2.3 MIL WHITE TOP-COATED BOPP	023WT	2.3 mil solid white top-coated BOPP. Compatible with UV and water-based flexo, and UV inkjet printing; also hot stamping. Exceptional opacity. Backside treated for adhesive anchorage. Great stiffness for auto application. Ideal for prime labeling.	2.3 58.0
2.4 MIL TOP COATED WHITE LABEL-LYTE™	024TL	A 2.4 mil glossy white BOPP top coated for ink adhesion. Has a distinctive pearlescent sheen. Excellent compatibility with UV curing inks and water based flexo ink systems. Label-Lyte is a Trademark of Jindal Films America.	2.4 61.0
2.6 MIL TOP COATED WHITE LABEL-LYTE™	026TL	A 2.6 mil glossy white BOPP top coated for ink adhesion. Has a distinctive pearlescent sheen. Excellent compatibility with UV curing inks and water based flexo ink systems. Label-Lyte is a Trademark of Jindal Films America.	2.6 69.0
3.6 MIL WHITE TC BOPP	036WG	A 3.6 mil white BOPP film. UV resistance and top coating suitable for UV screen, UV flexo and waterbased inks. Can be used for window graphics, or other applications where a more substantial film is needed.	3.6 91.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
FILMS: POLYPROPYLENES (WHITE) (cont.)			
2.4 MIL WHITE TOP-COATED BOPP	24WCB	2.4 mil white top-coated BOPP. Compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Backside coated for adhesive anchorage. Glossy look. Perfect for prime label applications; health and beauty aid, household care, and beverage labeling.	2.4 61.0
2.4 MIL WHITE TOP-COATED BOPP	24WCT	2.4 mil white top-coated BOPP. It is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Glossy look. Perfect for health and beauty aid, household care, and beverage labeling.	2.4 61.0
2.6 Mil WHITE TOP-COATED BOPP	26WCB	2.6 mil white top-coated BOPP. Compatible with water-based and UV flexo, and UV inkjet presses. Backside coated for adhesive anchorage. Glossy look. Perfect for prime label applications; health and beauty aid, household care, and beverage labeling.	2.6 66.0
2.6 MIL WHITE TOP-COATED BOPP	26WCT	2.6 mil white top-coated BOPP. It is compatible with water-based and UV flexo, and UV inkjet presses. Glossy look. Perfect for health and beauty aid, household care, and beverage labeling.	2.6 66.0
3.4 MIL MATTE WHITE INKJET BOPP	34WIJ	A 3.4 mil white matte BOPP that is a multi-purpose film for both water-based and pigment ink jet printing. Quick drying on press. The smooth surface allows graphics to really stand out on both black and white, and color printers. Good moisture resistance.	3.4 86.4

FILMS: POLYPROPYLENES (VARIABLE IMAGING)

2.9 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	70MKE	A 2.9 mil BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	2.9 73.7
3.3 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	84MBE	A 3.3 mil BOPP, no phenols added film, with direct thermal coating. Top coated for durability. Medium degree of sensitivity. Use when moisture and environmental resistance are important. Good stiffness for ease of dispensing. Dark image for excellent ability to be read and scanned.	3.3 83.8



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
FILMS: POLYPROPYLENES (VARIABLE IMAGING) (cont.)			
2.6 MIL THERMAL TRANSFER WHITE LABEL-LYTE™	026TT	2.6 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is required. Label-Lyte is a trademark of Jindal Films America.	2.6 66.0
THERMAL TRANSFER WHITE LABEL-LYTE™	030TT	White Label-Lyte BOPP with a thermal transfer top coat. Label-Lyte is a Trademark of Jindal Films America.	3.0 76.0
3.0 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	070MK	A 3.0 mil BOPP direct thermal film. Medium degree of sensitivity. Top coated for durability. Use when moisture and environmental resistance are important. Dark image for excellent ability to be read and scanned.	3.0 76.0
3.0 MIL TC MATTE WHITE BOPP	075WP	A 3.0 mil top coated matte white BOPP. A synthetic paper, it can be used with thermal transfer, flexography, screen, letterpress, and other print	3.0 75.0
3.3 MIL SYNTHETIC MEDIUM SENSITIVITY FILM	084MB	A 3.3 mil BOPP direct thermal film. Top coated for durability. Medium degree of sensitivity. Use when moisture and environmental resistance are important. Good stiffness for ease of dispensing. Dark image for excellent ability to be read and scanned.	3.3 84.0
SYNTHETIC MEDIUM SENSITIVITY FILM	095RK	4.1 mil white BOPP film with direct thermal coating. Top coated for durability. Medium degree of sensitivity.	4.1 104.0
TOP COATED KIMDURA® FPG 95	095TK	A 4.2 mil (92 g/m ²) Kimdura® BOPP specially top coated for thermal transfer, dot matrix, ion deposition and digital printing. Registered Trademark of Neenah Paper, Inc. © 2007 NPI All Rights Reserved.	4.2 107.0
SYNTHETIC MEDIUM SENSITIVITY FILM	096RK	4.1 mil white BOPP film with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	4.1 104.0
SYNTHETIC MEDIUM SENSITIVITY FILM	96RKE	4.0 mil white BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.	4.0 101.6



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
FILMS: POLYPROPYLENES (VARIABLE IMAGING) (cont.)			
MATTE WHITE BOPP	100WP	A 3.7 mil top coated matte white BOPP. UV resistant. For use with thermal transfer and other print methods. Consider for drum label, outdoor and other demanding applications.	3.7 95.0
FILMS: POLYPROPYLENES (METALIZED)			
1.85 MIL SILVER METALIZED BOPP	018MT	1.85 mil clear BOPP metalized on the back for durability. Top coated for print compatibility with water-based and UV flexo, and UV inkjet. Great stiffness for automatic application. Ideal for bright label graphics that will catch the eye of the consumer.	1.9 47.0
2.0 MIL SILVER METALIZED BOPP	021MU	A 2.0 mil BOPP metalized on the back side for a shiny silver appearance. Top coated for printability with a wide range of ink systems.	2.0 51.0
FILMS: POLYSTYRENES			
1.5 MIL CLEAR POLYSTYRENE	015PN	A 1.5 mil corona treated clear polystyrene. Perfect for use as a base for peel-off coupons and booklets.	1.5 38.0
2.0 MIL CLEAR POLYSTYRENE	020PN	A 2.0 mil corona treated clear polystyrene. Stiffness allows easy converting and dispensing.	2.0 51.0
2.5 MIL CLEAR POLYSTYRENE	025PN	A 2.5 mil corona treated clear polystyrene. Stiffness allows easy converting and dispensing. Great for use as a mailing tab.	2.5 64.0
2.5 MIL WHITE POLYSTYRENE	25PSW	A 2.5 mil corona treated white polystyrene. Stiffness allows easy converting and dispensing.	2.5 64.0
FILMS: POLYESTERS			
2 MIL CLEAR TOP COATED POLYESTER	020MY	A very clear, top coated polyester film. Top coating allows for printing with most standard flexo and UV letterpress inks.	2.0 51.0
2.0 MIL VALUE WHITE POLYESTER	2VWPT	A matte, white polyester film, top-coated for water-based and U.V. flexographic ink adhesion, and thermal transfer printing. Designed for durable applications – resistant to heat and chemicals. High tear strength.	2.0 50.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

FACESTOCK SELECTION GUIDE

Title	Code	Description	Target (MILS) (Microns)
FILMS: CLEAR SPECIALTY			
2 MIL CLEAR ACETATE	020AC	A 2.0 mil clear acetate film with good clarity and printability. It is compostable. Has relatively low tear resistance and is good for tamperproof applications. Meets the ASTM D6400 compost standard.	2.0 51.0
FILMS: WHITE SPECIALTY			
TYVEK®	046TV	DuPont™ Tyvek® (1073D) is a 7.5 mil, strong, translucent polyolefin with exceptional strength and moisture resistance. DuPont™ and Tyvek® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.	7.6 191.0
PIGGYBACKS			
54# SEMI-GLOSS	054SG	54# (78 g/m ²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, UV letterpress, and offset methods. FSC®-certified paper.	2.6 66.0
60# DULL LITHO	061DL	60# (89 g/m ²) high quality, dull finish litho offering excellent print and die-cut properties. Good for flexographic and offset printing. FSC®-certified paper.	3.0 76.0
VALUE THERMAL TRANSFER	VALUT	A 42# (62 g/m ²) top-coated, thermal transfer sheet that offers high performance at a lower cost. Strength and opacity are comparable to conventional thermal transfer facers. Exceptional print quality, especially for flood coating. FSC®-certified paper.	2.8 70.0



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

ADHESIVE SELECTION GUIDE

	Minimum Application Temp	Service Temp Range	Description
COLD-TEMP			
00552	-20°F -29°C	-65° to +120°F -54° to +49°C	Acrylic freezer adhesive used in many film wrapped meat and dairy applications, including the more difficult blast freeze environment.
00720	-20°F -29°C	-65° to +180°F -54° to +82°C	A soft, general purpose, all-temperature acrylic adhesive for paper and film labels. Adheres to a variety of packages in a broad range of temperatures. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.
0720M	-20°F -29°C	-65° to +180°F -54° to +82°C	A versatile cold-temperature acrylic adhesive that adheres to many packaging materials in a broad range of temperatures. Faster stripping than many cold-temp adhesives. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.
00853	0°F -18°C	-50° to +125°F -46° to +52°C	A cold-temperature acrylic adhesive, designed to run cleanly on press. Perfect for weigh scale applications.
0976S	-20°F -29°C	-65 to +180°F -54 to +82°C	All-temperature acrylic adhesive designed for PET, Colored HDPE, and PP recycling. Will wash off PET clamshells, bottles, and other containers. Carries APR critical guidance approval for PET, Colored HDPE and PP recycling when paired with clear, white, and metalized BOPP films.

PERMANENT			
00103	+40°F + 4°C	-65° to +200°F -54° to +93°C	A soft, high performance film label acrylic adhesive with excellent clarity and adhesion to low energy surfaces, along with outstanding wet-out.
00406	+10°F -12°C	-40° to +300°F -40° to +150°C	A permanent acrylic adhesive designed for film face stocks used in durable applications. Has high tack and excellent adhesion to low energy surfaces. An environmentally-friendly alternative to solvent adhesives.
00504	+35°F + 2°C	-40° to +160°F -40° to +71°C	A general purpose acrylic emulsion used primarily with paper substrates.
00506	+45°F + 7°C	-65° to +200°F -54° to +93°C	A general purpose acrylic emulsion adhesive with good UV stability. Non-yellowing, and generally used with film face stocks.
00508	+45°F + 7°C	-65° to +200°F -54° to +93°C	A hard, acrylic adhesive. Useful for prime label pharmaceutical (pill bottles). Good for curved surfaces greater than 1/2" diameter requiring mandrel hold. Offers some reposition time on low-energy plastics. Glove friendly.



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. Coated Products Operations, Roll Printer Price Book) in effect at the

May 18, 2026

ADHESIVE SELECTION GUIDE

Minimum Application Temp	Service Temp Range	Description
PERMANENT (cont.)		
00515 +40°F +4°C	-40° to +250°F -40° to +121°C	A permanent, acrylic adhesive that has good water whitening resistance and adheres well to low surface energy plastics. Good combination of quick tack and high shear makes it ideal for mailing tabs.
00525 +45° F +7°C	-65°F to +200°F -54°C to +93°C	A general purpose permanent, pharmaceutical acrylic adhesive. A higher coat weight version of 508. This adhesive is ideal for rough surfaces. Holds tight in difficult, small diameter applications. Repositionable on some surfaces.
00600 -20°F -29°C	-65° to +180°F -54° to +82°C	A permanent acrylic adhesive, which removes from glass bottles in a 100°F water bath. Designed for wine and other beverage labeling. Can be used in a wide range of temperatures, including cold applications. Removal times depend on facer and bottle type.
00700 +35°F +2°C	-65° to +200°F -54° to +93°C	A general purpose acrylic emulsion for paper. Repositions on many low energy plastics.
00747 0°F -18°C	-65° to +200°F -54° to +93°C	A general purpose, acrylic permanent that displays excellent adhesion over a broad temperature range while providing aggressive performance. Perfect for wine labeling, as it can withstand ice bucket conditions.
00751 +45°F +7°C	-65° to +200°F -54° to +93°C	A paper and film compatible acrylic with good adhesion to many substrates. Excellent die-cutting and stripping. Exceptional mandrel hold.
00757 +32°F 0°C	-58° to +199°F -50° to +93°C	A permanent acrylic adhesive with an aggressive bond to many surfaces, including low-energy plastics and corrugated. Harder adhesive for clean converting. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.
00950 +25°F -4°C	-40° to +160°F -40° to +71°C	General purpose filmic adhesive designed for prime label applications. High shear properties leading to excellent press convertibility. Provides good open time for label repositioning. Performs at application temperatures as low as 25°F. Meets APR Preferred Design for Recycling on HDPE (colored) and PP substrates.
00960 +14°F -10°C	-40° to +160°F -40° to +71°C	General purpose filmic adhesive designed for prime label applications. Excellent clarity and improved blush resistance. Higher shear film adhesive for improved press convertibility. Performs at application temperatures as low as 14°F. Meets APR Preferred Design for Recycling on HDPE (colored) and PP substrates.
0758M +35°F +2°C	-65° to +200°F -54° to +93°C	An acrylic general purpose permanent adhesive with great die-cutting and stripping properties. Adheres well to many substrates, including corrugated.



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. Coated Products Operations, Roll Printer Price Book) in effect at the

May 18, 2026

ADHESIVE SELECTION GUIDE

	Minimum Application Temp	Service Temp Range	Description
PERMANENT (cont.)			
0776S	+25°F -4°C	-65° to +200°F -54° to +93°C	A general purpose acrylic adhesive designed for PET recycling. Will wash off PET clamshells, bottles, and other containers during recycling leaving no adhesive residue behind. When combined with specific facers it has APR Critical Guidance Recognition.
767HM	+20°F -7°C	-65° to +165°F -54° to +74°C	A highly versatile rubber-based hot melt adhesive with quick tack. It stands up to moisture and adheres securely to both low-energy and textured surfaces.
REMOVABLE			
00272	+20°F -7°C	-10° to +120°F -23° to +49°C	Non-toxic paper removable microsphere acrylic adhesive with good clean removal. Great choice for kiddie stickers, business forms, and price labels.
00275	+35°F +2°C	+20° to +120°F -7° to +49°C	Most universal acrylic microsphere adhering to corrugated, glass, metal, and plastics. No residue on glass or credit cards. Repositionable. Not recommended for small labels, or flood coated applications. Repulpable when applied to paper face stocks.
00278	+20°F -7°C	-10 to +120°F -23 to +49°C	Ultra-removable microsphere acrylic adhesive for paper face stocks. Adheres to, and removes cleanly from, a variety of substrates. Perfect for kiddie stickers, and short-term labeling such as price marking, promotions, and logistics.
00347	+35°F +2°C	-40° to +180°F -40° to + 82°C	Specialized removable acrylic for film face stocks. Has low peel and no-build properties. Designed for clean and easy removal from glass even after extended periods of time and temperature changes.
00531	+40°F +4°C	+1° to +140°F -17° to + 60°C	General purpose removable acrylic adhesive for use with paper or film face stocks. Removes from some glass, plastic, and textile surfaces.
00532	+35°F +2°C	-40° to +160°F -40° to + 71°C	Textile acrylic adhesive that removes cleanly from most fabrics. Not recommended for leather, suede or silk. Be sure to test. All textile applications are different.
00538	+45°F +7°C	+1° to +160°F -17° to +71°C	A moderate-to-tight acrylic removable for use with films and strong paper face stocks.
00611	+21°F -6°C	-40° to +172°F -40° to +78°C	A water dissolvable acrylic adhesive. It adheres to, and washes off, many substrates including most plastics, stainless steel and glass. Combined with the dissolvable facer, H2ODP, the label disappears in 30 seconds. Can be used with other face stocks.



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. Coated Products Operations, Roll Printer Price Book) in effect at the

May 18, 2026

ADHESIVE SELECTION GUIDE

	Minimum Application Temp	Service Temp Range	Description
REMOVABLE (cont.)			
00633	+30°F -1°C	-65° to +200° F -54° to +93° C	An aggressive removable acrylic adhesive with a clean release for paper and film labels. It adheres to, and removes from, a wide variety of surfaces. Does not ghost. Good mandrel hold. Ideal for resealable closure labels.
00805	0°F -18°C	-50° to +125°F -46° to +52°C	A lighter tack acrylic adhesive for kiddie stickers. Can also be used for other applications requiring short-term removability. Works in a wide range of temperatures.
0900T	+30°F -1°C	-65°F to 200°F -54°C to 93°C	SimpleSeal™ 900T is a removable adhesive with clean release from a variety of surfaces. Low odor with good initial tack and a smooth, strong peel for dry reclosure applications
80361	0°F -18°C	-50° to +125°F -46° to +52°C	Acrylic adhesive designed for short-term removability. Consider for kiddie stickers.
RECYCLABLE			
00611	+21°F -6°C	-40° to +172°F -40° to +78°C	A water dissolvable acrylic adhesive. It adheres to, and washes off, many substrates including most plastics, stainless steel and glass. Combined with the dissolvable facer, H2ODP, the label disappears in 30 seconds. Can be used with other face stocks.
00720	-20°F -29°C	-65° to +180°F -54° to +82°C	A soft, general purpose, all-temperature acrylic adhesive for paper and film labels. Adheres to a variety of packages in a broad range of temperatures. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.
00757	+32°F +0°C	-58° to +199°F -50° to +93°C	A permanent acrylic adhesive with an aggressive bond to many surfaces, including low-energy plastics and corrugated. Harder adhesive for clean converting. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.
0720M	-20°F -29°C	-65° to +180°F -54° to +82°F	A hard, versatile cold-temperature acrylic adhesive that adheres to many packaging materials in a broad range of temperatures. Faster stripping than many cold-temp adhesives. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.
0776S	+25°F -4°C	-65° to +200°F -54° to +93°C	A general-purpose acrylic adhesive designed for PET recycling. Will wash off PET clamshells, bottles, and other containers during recycling leaving no adhesive residue behind. When combined with specific facers it meets APR Critical Guidance protocol.
0976S	-20°F -29°C	-65 to +180°F -54 to +82°C	All-temperature acrylic adhesive designed for PET, Colored HDPE, and PP recycling. Will wash off PET clamshells, bottles, and other containers. Carries APR critical guidance approval for PET, Colored HDPE and PP recycling when paired with clear, white, and metalized BOPP films.



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging, Inc. Coated Products Operations, Roll Printer Price Book) in effect at the

May 18, 2026

LINER SELECTION GUIDE

Title	Code	Target (Mils) (Microns)	Description
PAPER ROLL-TO-ROLL			
1.7 MIL WHITE GLASSINE	17GL	1.7 43.0	A 28# (45 g/m ²) white glassine provides an excellent surface for die-cutting. The thinner gauge allows more labels on a roll, and the lighter weight provides lower shipping costs saving you and your customers time and money.
2.4 MIL NATURAL KRAFT LINER	39NK	2.4 61.0	Produced without bleaching, this is a more environmentally-friendly, 39# (64 g/m ²) super calendered densified kraft liner offering good die-cutting and stripping. Can be recycled with corrugated.
2.4 MIL SEMI-BLEACHED DENSIFIED KRAFT	40SC	2.4 61.0	A white densified kraft sheet 41# (67 g/m ²) with excellent point-to-point caliper control.
41# WHITE KRAFT LINER	41WK	2.7 69.0	A premium, 41# (66 g/m ²) white kraft liner that is designed for roll-to-roll and fan-fold applications. Outstanding performance die cutting both paper and film.
3.2 MIL SEMI-BLEACHED DENSIFIED KRAFT	50SC	3.2 81.0	A white densified kraft sheet 53# (86 g/m ²) with excellent point-to-point caliper control.
PAPER ROLL-TO-SHEET			
3.4 MIL LASER LINER	0PBLF	3.4 87.0	A premium, 50# (82 g/m ²) white kraft liner that is designed for roll-to-sheet and fan fold applications. Ideal for smooth feeding in desktop laser and inkjet printers. Suitable for die cutting both paper and film.
3.2 MIL CLAY COATED LAY FLAT	0PRLF	3.2 82.0	A premium, 53# (87 g/m ²) white kraft liner. Suitable for roll-to-sheet and fan fold applications. Designed for four-color process printing on the back side. Can be used for die cutting both paper and film.
3.2 MIL KRAFT LAY FLAT	32KLF	3.2 81.0	Designed for roll-to-sheet and fan fold applications, 32KLF is a premium, white kraft 45# (73 g/m ²) liner. It is back side printable. This liner can be used with both paper and film facestocks.
2.7 MIL LASER LINER	41LF	2.7 69.0	A premium, 41# (66 g/m ²) white kraft liner that is designed for roll-to-sheet and fan fold applications. Ideal for smooth feeding in desktop laser and inkjet printers. Suitable for die cutting both paper and film.
3.2 MIL PRINTABLE LAY FLAT LINER	53CRT	3.2 81.0	A 54# (88 g/m ²) blue-white kraft liner. Good dimensional stability for roll-to-sheet lay flat applications. Features a coated back side for a premium appearance and flexo printability. Suitable for charity mailing labels.



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

LINER SELECTION GUIDE

Title	Code	Target (Mils) (Microns)	Description
PAPER ROLL-TO-SHEET (cont.)			
3.5 MIL CLAY COATED LAY FLAT	60LF	3.5 88.0	A 56# (92 g/m ²) liner with high white visual appeal. Ideal for sheeted or fan fold applications. Designed for four-color process printing on the back side.
4.6 MIL LAY FLAT LINER	74LF	4.6 117.0	A white 74# (121 g/m ²) kraft liner that offers good dimensional stability for roll-to-sheet applications. Perfect for facer materials and applications that need extra rigidity to lay flat.
FILM			
1.2 MIL CLEAR POLYESTER	12NB	1.2 30.0	Clear polyester with an excellent surface for die-cutting. Great strength for high speed converting and application.
1.2 MIL CLEAR POLYESTER	12PE	1.2 31.0	Clear polyester liner with a firm surface for die-cutting. Easy release for high speed converting and application.
1.4 MIL CLEAR POLYESTER	15PT	1.4 36.0	Clear polyester liner with an excellent surface for die-cutting and high speed automatic applications.
.92 MIL CLEAR POLYESTER	92NB	0.9 23.0	Clear polyester with an excellent surface for die-cutting. Great strength for high speed converting and application. The benefits of this thinner gauge liner include reducing plastic use, decreasing shipping weight, and allowing more labels on a roll.
POLY KRAFT			
3.1 MIL NATURAL KRAFT/POLYPROPYLENE	44PM	3.1 72.0	A 44# (72 g/m ²) natural kraft liner extrusion coated with polypropylene. Designed to prevent V-type tears and is an excellent choice for high speed automatic applications. Commonly used in wine label applications.



Green Bay Packaging Inc.
Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
WHITE PAPERS - SEMI-GLOSS										

53# SEMI-GLOSS

53# (78 g/m²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, toner, and offset methods. FSC®-certified paper.

054SG	00278	40SC	S8164560	227	I					
054SG	00508	40SC	S7558760	235	C					
054SG	00532	40SC	S8280160	230	C					
054SG	00552	40SC	S9931260	236	C					
054SG	00633	40SC	S9175160	233	I					
054SG	00700	40SC	S7755860	239	I					
054SG	00720	40SC	S7724460	229	I	I	I	I	I	I
054SG	00720	12NB	S8121860	196	C					
054SG	00751	40SC	S7748960	239	I	I		I	I	I
054SG	00751	12NB	S8823660	200	I					
054SG	00751	40SC	S8895960	235	C				I	
054SG	00805	0PRLF	S8941160	258	I					
054SG	0720M	40SC	S8849360	232	I	I			I	I
054SG	0720M	12NB	S8898960	196	I	I	I			I
054SG	0758M 0758M	40SC 50SC	S7686660	379	C					
054SG	0758M 0758M	40SC 40SC	S8027060	361	I					
054SG	0758M	0PRLF	S8082660	262	I	I	I			
054SG	0758M	41LF	S9176660	235	I					
054SG	80361	0PRLF	S8001560	262	I					

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
WHITE PAPERS - SEMI-GLOSS										

58# SEMI-GLOSS

58# (87 g/m²) semi-gloss multi-purpose paper with superior gloss and print qualities. Bright blue-white shade. Excellent graphic results with flexo, offset, or toner-based printing. FSC®-certified paper.

060SG	00720	40SC	S7804560	240	I	I				
060SG	00747	40SC	S7813460	247	C					
060SG	00751	40SC	S7821360	246	C					
060SG	0720M	40SC	S8899160	246	I	I	I			I
060SG	0758M	60LF	S8003760	280	C					

80# SEMI-GLOSS

80# (118 g/m²) semi-gloss multi-purpose paper with superior gloss and print qualities. Bright blue-white shade. Excellent print surface for flexo, toner, or offset. This heavier sheet offers greater stiffness and opacity. FSC®-certified paper.

080SG	00720	40SC	S8153960	288	C					
080SG	00751	60LF	S8732360	331	C					
080SG	0758M	40SC	S8098160	294	C					

FSC® CERTIFIED 53# SEMI-GLOSS PAPER

53# (78 g/m²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, toner, and offset methods. FSC®-certified paper.

F54SG	00720	40SC	S8792860	231	C					
F54SG	00747	40SC	S7739560	233	I	I				

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

WHITE PAPERS - SEMI-GLOSS

60# SEMI-GLOSS WITH 30% POST-CONSUMER WASTE

A 60# (89 g/m²) semi-gloss face stock with 30% post-consumer recycled fiber. Excellent strength characteristics enhance label converting and application. Smooth print surface for outstanding graphics. FSC®-certified paper.

R60SG	00720	40SC	S8187460	247	C					
R60SG	00720	39NK	S8743660	243	C	I				

WHITE PAPERS - MATTE

60# LITHO MATTE

A 60# (89 g/m²) clay-coated matte smooth paper. Offers a great printing surface for excellent graphic reproduction. Its very matte appearance provides a unique look in package design. Perfect for flexo printing and in a variety of digital presses.

060LM	00720	40SC	S8842760	250	C					
060LM	00751	40SC	S8830560	248	C					

60# DULL LITHO

60# (89 g/m²) high quality, dull finish litho offering excellent print and die-cut properties. Good for flexographic and offset printing. FSC®-certified paper.

061DL	00504	40SC	S7754060	253	C					
061DL	00700	40SC	S7746460	253	C					
061DL	00720	40SC	S4331060	246	I					
061DL	00751	40SC	S7752260	250	C					
061DL	0758M	0PRLF	S8003060	277	C					
061DL	0758M	40SC	S8769360	248	I					

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA
 WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

I - Inventory
 C - Custom
 I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

WHITE PAPERS - INDIGO TOPCOATED

INDIGO TOPCOATED 55# SEMI-GLOSS

55# (81 g/m²) semi-gloss sheet designed for printing on HP Indigo presses. It has been certified by RIT for use on the ws4500 and ws6000 presses. Has a blue-white shade with high brightness and opacity. Exceptionally strong. FSC®-certified paper.

D55SG	00720	40SC	S8142460	237	C					
D55SG	00751	40SC	S8126960	237	C					

TAG STOCK

8 POINT GLOSS WHITE CLAY COATED TAG

A glossy, bright white, 130# (192 g/m²) board with excellent print characteristics. Coated on both sides, allowing for multiple uses - as a tag, or in a pressure-sensitive structure. FSC®-certified paper.

008GB	00504	40SC	S9941860	398	I					
008GB	00532	40SC	S9941260	395	C					
008GB	00751	40SC	S7666660	400	C					
008GB			S7670560	273	C					

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			■ TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
FLUORESCENT PAPERS										

BLUE FLUORESCENT

57# (84 g/m²) blue matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. Unique color makes labels stand out. Offers another option when using color coded labels. FSC®-certified paper.

054BZ	00720	40SC	S8122860	242	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

GREEN FLUORESCENT

57# (84 g/m²) green matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.

054GZ	00720	40SC	S6231060	242	I					
054GZ	00720	40SC	S7656360	242	C			I		I
054GZ	0758M	0PBLF	S8189860	262	I					

ORANGE FLUORESCENT

57# (84 g/m²) orange matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.

054OZ	00720	40SC	S6235060	242	I					
054OZ	00720	40SC	S7607960	242	C					I
054OZ	0758M	0PBLF	S8190060	262	I					

PINK FLUORESCENT

57# (84 g/m²) pink matte fluorescent coated paper. Designed for laser, price marking, inkjet, promotional and general roll label applications. FSC®-certified paper.

054PZ	00720	40SC	S7748660	242	C					I
054PZ	00720	40SC	S8034360	238	I					
054PZ	0758M	0PBLF	S8190160	262	I					

Locations: GB - Green Bay, WI WIN - Winchester, VA	KC - Kansas City, MO MIN - Minneapolis, MN	ATL - Atlanta, GA LA - Los Angeles, CA	I - Inventory C - Custom I TIP Item
---	---	---	---

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
BEER & WINE LABEL										

ESTATE LABEL* #4 WHITE LAID

60# (89 g/m²) white, laid, uncoated, wet strength paper. Maintains its visual integrity when wet. Perfect for wine and beer labels. Its high-end look matches well with upscale products. *Registered Trademark of Neenah Paper, Inc. FSC®-certified paper.

0WEL4	00747	44PM	S8748260	258	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

ESTATE LABEL* #8 WHITE SMOOTH

60# (89 g/m²) uncoated, white, wet strength paper. Maintains its integrity when wet. Designed for wine and other high-end labels, such as gourmet foods and cosmetics. *Registered Trademark of Neenah Paper, Inc. FSC®-certified paper.

0WEL8	00747	44PM	S8266860	258	I					I
-------	-------	------	----------	-----	---	--	--	--	--	---

ESTATE LABEL* #9 CREAM LAID

60# (89 g/m²) uncoated cream wet strength paper. Maintains its integrity when wet. Perfect for wine and other upscale labels, such as gourmet foods and cosmetics. FSC®-certified paper. *Registered Trademark of Neenah Paper, Inc.

0WEL9	00747	44PM	S8742160	258	I					I
-------	-------	------	----------	-----	---	--	--	--	--	---

SILVER METALIZED WET STRENGTH PAPER

56# (83 g/m²) top coated silver metalized paper. Wet strength for use in moist environments including refrigerated foods and chilled beverages. The metallic look makes a product's graphics stand out. Not recommended for HP Indigo Presses.

56MSW	00720	40SC	S8982560	239	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

70# BRIGHT WHITE FELT

70# (103 g/m²) uncoated bright white, wet strength paper. Perfect for wine, beer, and other beverage labels. The rich weight and texture makes it ideal for upscale food, home, and personal care products. FSC®-certified paper.

70BWF	00747	44PM	S8903652	279	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

70BWF	00747	12NB	S8903752	237	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations:	GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
	WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
				TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
BEER & WINE LABEL										

60# BLACK VELLUM

60# (89 g/m²) uncoated, black, smooth, wet strength paper. Maintains its integrity when wet. While it was designed for wine, beer, and other beverage labels, its unique look will make any product stand out on store shelves. FSC®-certified paper.

BKVLM	00747	40SC	S8909252	250	C					
BKVLM	00747	44PM	S8936852	258	C					

50# KONA LIGHT ROAST

KONAL is a 50# (74g/m²), 100% PCW recycled wet strength product. A blend of repurposed coffee bean bag fiber and post-consumer waste material. Perfect for labeling any coffee-related product, or environmentally-friendly packaging. FSC®-certified paper.

KONAL	00720	39NK	S8796760	227	I					
KONAL	00747	40SC	S8939760	232	C					

60# 100% PCW WET STRENGTH PAPER

A 60# (89 g/m²) FSC®-certified, 100% post-consumer waste paper with wet strength. Resistant to moisture, it's perfect for beverage applications, like wine, beer and chilled spirits. Its luxurious look will enhance upscale food and personal care products.

PLRNB	00720	39NK	S9089960	248	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

SPECIALTY PAPERS

54# WET STRENGTH SEMI-GLOSS

54# (80 g/m²) C1S blue-white semi-gloss. Wet strength stands up to moisture. Ideal for chilled beverages, including beer and wine, or refrigerated foods. Smooth surface enhances print results with flexo, laser and other press types. FSC®-certified paper.

054WS	00747	40SC	S8901460	238	C					
054WS	00747	12NB	S8906760	202	C					

Locations: GB - Green Bay, WI WIN - Winchester, VA	KC - Kansas City, MO MIN - Minneapolis, MN	ATL - Atlanta, GA LA - Los Angeles, CA	I - Inventory C - Custom TIP Item
---	---	---	---

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
SPECIALTY PAPERS										

BROWN NATURAL KRAFT

60# (89 g/m²) brown natural kraft paper. The natural look makes it perfect for labeling organic or other earth-friendly products. It can also be used for cover-up labels on corrugated containers.

060GM	00720	40SC	S8083760	260	C		I			I
060GM	0758M	40SC	S7649360	264	I					

TRANSLUCENT PAPER

A 42# (62 g/m²) ultra-clear translucent paper. It is well-suited for wafer seal mailing tabs. Can be used for tamper-evident seals. Also provides a unique look for primary package decoration.

1TRCT	00515	40SC	S9204660	211	C					
1TRCT	00751	40SC	S9193960	204	C					
1TRCT	00757	40SC	S9189960	208	C					

DISSOLVABLE PAPER

A water-soluble paper. Coated with the dissolvable adhesive, 611, it disappears in seconds under running water. Leaves no residue on the container. Best dissolvable performance when printed with water-based inks. Keep wrapped until used. FSC®-certified.

H2ODP	00611	40SC	S8210460	206	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

50# KONA LIGHT ROAST

KONAL is a 50# (74g/m²), 100% PCW recycled wet strength product. A blend of repurposed coffee bean bag fiber and post-consumer waste material. Perfect for labeling any coffee-related product, or environmentally-friendly packaging. FSC®-certified paper.

KONAL	00720	39NK	S8796760	227	I					
KONAL	00751	39NK	S8841160	228	C					

Locations: GB - Green Bay, WI WIN - Winchester, VA	KC - Kansas City, MO MIN - Minneapolis, MN	ATL - Atlanta, GA LA - Los Angeles, CA	I - Inventory C - Custom I TIP Item
---	---	---	---

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

LAMINATED FOILS

BRIGHT GOLD FOIL

Top coated 70# (104 g/m²) bright gold laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.

055BG	00720	40SC	S6301060	275	I					I
-------	-------	------	----------	-----	---	--	--	--	--	---

BRIGHT SILVER FOIL

Top coated 70# (104 g/m²) bright silver laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.

055BS	00720	40SC	S6299060	275	I					I
055BS	00751	40SC	S5732060	278	C					

DULL GOLD FOIL

Top coated 70# (104 g/m²) dull gold laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.

055DG	00720	40SC	S6300060	275	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

DULL SILVER FOIL

Top coated 70# (104 g/m²) dull silver laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.

055DS	00720	40SC	S6306060	275	I	I				I
055DS	00751	40SC	S4601060	278	C					I

FOIL SUBSTITUTES

1.85 MIL SILVER METALIZED BOPP

1.85 mil clear BOPP metalized on the back for durability. Top coated for print compatibility with water-based and UV flexo, and UV inkjet. Great stiffness for automatic application. Ideal for bright label graphics that will catch the eye of the consumer.

018MT	00720	40SC	S9036760	178	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI WIN - Winchester, VA	KC - Kansas City, MO MIN - Minneapolis, MN	ATL - Atlanta, GA LA - Los Angeles, CA	I - Inventory C - Custom TIP Item
---	---	---	---

Additional hologram patterns available: Minimum customer order Qty is 18 MMSI Please allow 4 to 6 weeks for delivery

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

FOIL SUBSTITUTES

2.0 MIL SILVER METALIZED BOPP

A 2.0 mil BOPP metalized on the back side for a shiny silver appearance. Top coated for printability with a wide range of ink systems.

021MU	00720	40SC	S8031460	184	I					
021MU	00751	40SC	S7345060	188	C					

HOLOGRAM PRISMATIC DIFFRACTION: RAINBOW

64# (94 g/m²) decorative prismatic diffraction paper. Shim lines/seams are present in holographic material. This gap in the pattern will be up to 1/32" wide. The area between the shim lines measures 30" machine direction (MD) and 48" cross direction (CD).

056H5	00751	40SC	S4607060	250	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

56# SILVER METALIZED PAPER

56# (83 g/m²) top coated silver metalized paper. Not recommended for HP Indigo Presses.

057MS	00720	40SC	S6203060	239	I					
057MS	00751	40SC	S5841060	242	I					

SILVER METALIZED WET STRENGTH PAPER

56# (83 g/m²) top coated silver metalized paper. Wet strength for use in moist environments including refrigerated foods and chilled beverages. The metallic look makes a product's graphics stand out. Not recommended for HP Indigo Presses.

56MSW	00720	40SC	S8982560	239	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI WIN - Winchester, VA	KC - Kansas City, MO MIN - Minneapolis, MN	ATL - Atlanta, GA LA - Los Angeles, CA	I - Inventory C - Custom TIP Item
---	---	---	---

Additional hologram patterns available: Minimum customer order Qty is 18 MMSI Please allow 4 to 6 weeks for delivery

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

THERMAL TRANSFER

2.6 MIL THERMAL TRANSFER WHITE LABEL-LYTE™

2.6 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is required. Label-Lyte is a trademark of Jindal Films America.

026TT	00747	40SC	S8773660	192	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

THERMAL TRANSFER WHITE LABEL-LYTE™

3.0 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is important. Label-Lyte is a Trademark of Jindal Films America.

030TT	00747	40SC	S5213060	199	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

HIGH SPEED COATED THERMAL TRANSFER

47# (70 g/m²) premium bright white, coated, ultra-smooth thermal transfer paper stock offering broad ribbon compatibility. FSC®-certified paper.

050HS	00272	40SC	S7019060	218	I					
050HS	00275	41WK	S9156260	214	I					
050HS	0758M	40SC	S7699560	227	C					

3.0 MIL TC MATTE WHITE BOPP

A 3.0 mil top coated matte white BOPP. A synthetic paper, it can be used with thermal transfer, flexography, screen, letterpress, and other print methods. It is moisture, chemical and tear resistant.

075WP	00747	40SC	S8149152	211	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			■ TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

THERMAL TRANSFER

TOP COATED KIMDURA® FPG 95

A 4.2 mil Kimdura® BOPP specially top coated for thermal transfer, dot matrix, ion deposition and digital printing. Registered Trademark of Neenah Paper, Inc. © 2007 NPI All Rights Reserved.

095TK	00506	40SC	S3252060	256	I					
095TK	00506	50SC	S3256060	272	C					
095TK	00538	50SC	S3286060	272	I					
095TK	00751	50SC	S5391060	273	I					

SELECT THERMAL TRANSFER OPAQUE

A 44# (65 g/m²) gray opaque multi-purpose thermal transfer sheet. Designed for cover up labels, with excellent opacity. Premium coating for enhanced flexo graphics. FSC®-certified paper.

0TTFA	0758M	40SC	S7711260	218	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

SELECT THERMAL TRANSFER

A 44# (65 g/m²) multi-purpose thermal transfer sheet. Premium coating for enhanced flexo-printed graphics. FSC®-certified paper.

0TTFP	00531	40SC	S7843160	216	I					
0TTFP	00700	40SC	S6745060	218	C			I		
0TTFP	00720	40SC	S7833160	210	I		I			
0TTFP	00751	40SC	S6613060	216	C					
0TTFP	0758M	40SC	S7664660	218	I	I	I	I		I

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			■ TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

THERMAL TRANSFER

MATTE WHITE BOPP

A 3.7 mil top coated matte white BOPP. UV resistant. A synthetic paper, it can be printed by thermal transfer, flexography, screen, and letterpress. Moisture, chemical and tear resistant. For drum label, outdoor and other demanding applications.

100WP	00720	40SC	S8204960	222	C					
100WP	00747	50SC	S7604660	247	C					
100WP	00747	40SC	S7605960	229	I					
100WP	00751	40SC	S7206060	226	C					

VALUE THERMAL TRANSFER

A 42# (62 g/m²), top-coated thermal transfer sheet that offers high performance at a lower cost. Strength and opacity are comparable to conventional thermal transfer facers. Exceptional print quality, especially for flood coating. FSC®-certified paper.

VALTE	00720	40SC	S9216160	209	I	I			I	I
VALTE	00757	40SC	S9244860	214	I	I	I		I	I

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

DIRECT THERMAL

DIRECT THERMAL PRESCRIPTION VIAL LABEL

This 48# (71 g/m²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.

021RX	00751	40SC	S9174660	229	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

RED FLUORESCENT DIRECT THERMAL

A 54# (80 g/m²) bright red direct thermal coated paper. Images black. Intended for attention-grabbing promotional point-of-purchase labels, or color coded warehouse tracking. FSC®-certified paper.

022FT	00720	40SC	S9127860	229	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

PREMIUM TOP COATED TD

A 53# (78 g/m²) top coated direct thermal coated paper for more demanding applications and higher imaging speeds. FSC®-certified paper.

022TD	00720	40SC	S6290060	232	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

ECONOMY TOP COATED DIRECT THERMAL PAPER

A 53# (78 g/m²) top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.

024DT	00720	40SC	S8814460	0						
-------	-------	------	----------	---	--	--	--	--	--	--

3.0 MIL SYNTHETIC MEDIUM SENSITIVITY FILM

A 3.0 mil BOPP direct thermal film. Medium degree of sensitivity. Top coated for durability. Use when moisture and environmental resistance are important. Dark image for excellent ability to be read and scanned.

070MK	00720	40SC	S4335060	202	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

SYNTHETIC MEDIUM SENSITIVITY FILM

4.1 mil white BOPP film with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.

096RK	00720	40SC	S9177360	223	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			■ TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

DIRECT THERMAL

SYNTHETIC MEDIUM SENSITIVITY FILM

4.0 mil white BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.

96RKE	00504	40SC	S9285360	243	C					
96RKE	00720	40SC	S9271460	238	I	I				

TOP COATED VALUE DIRECT THERMAL

A 48# (71 g/m²) top coated paper. Resists moisture, heat, humidity, fading, scuffing, chemicals, and plasticizers. Use for weigh scale applications, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper.

24VTB	00853	40SC	S9170460	0						
-------	-------	------	----------	---	--	--	--	--	--	--

DIRECT THERMAL (NO PHENOLS ADDED)

2.9 MIL SYNTHETIC MEDIUM SENSITIVITY FILM

A 2.9 mil BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.

70MKE	00720	40SC	S9272960	196	I		I			I
70MKE	00751	40SC	S9288560	200	I					

DIRECT THERMAL PRESCRIPTION VIAL LABEL

This 48# (71 g/m²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.

20RXE	00751	40SC	S9229660	226	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

DIRECT THERMAL PRESCRIPTION VIAL LABEL

This 48# (71 g/m²), no phenols added, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.

021RX	00508	40SC	S9174760	229	C		I			I
021RX	00751	40SC	S9174660	229	I					

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA
 WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

I - Inventory
 C - Custom
 I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
DIRECT THERMAL (NO PHENOLS ADDED)										
NEAR IR PACKAGE DELIVERY DIRECT THERMAL										
A 48# (70 g/m ²), no phenols added, direct thermal paper top-coated for handling durability. Near IR designed for package delivery. PCS and scanning up to 670 nm. For high-heat environments. Resists imaging up to 100°C. Moderate to fast print speeds. FSC®-certified paper.										
22PDE	00757	40SC	S9253852	227	C					
ECONOMY TOP COATED DIRECT THERMAL PAPER										
A 48# (72 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, alcohol and heat. Ideal for shipping and warehousing applications. FSC®-certified paper.										
23DTE	00720	40SC	S9231660	219	I	I				
ECONOMY TOP COATED DIRECT THERMAL PAPER										
A 50# (74 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.										
24DTE	00720	40SC	S9250760	214	I	I			I	I
ECONOMY TOP COATED DIRECT THERMAL PAPER										
A 49# (72.5 g/m ²), no phenols added, top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.										
25DTE	00751	40SC	S9254260	226	I					
25DTE	00757	40SC	S9254160	221	I	I				
25DTE	0720M	40SC	S9247160	217	I	I	I	I	I	I

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
INK JET / LASER										

Recommendations for Storage and Handling of Layflat Label Material

- * Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- * The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- * Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- * Rotate your stock. Use oldest inventory first.
- * Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- * INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

50# LASER JET WITH 100% PCW

A 50# (74 g/m²) multi-purpose facer for laser and inkjet printing. Produced with 100% post-consumer waste. Has a bright, white color, so it is attractive while helping the environment. FSC® certified.

R51LJ	00757	0PBLF	S9241660	254	C					
-------	-------	-------	----------	-----	---	--	--	--	--	--

SUPER BRIGHT LASER JET

51# (75 g/m²) Exceptionally bright, uncoated, multi-purpose sheet for both laser and ink jet printing. FSC®-certified paper.

050LJ	00720	0PBLF	S8214960	249	I					
050LJ	00751	0PBLF	S8218060	255	I		I			I
050LJ	00757	0PBLF	S9207460	254	I					
050LJ	0758M	0PBLF	S8165060	253	I					
050LJ	0758M	41LF	S8238360	233	C					
050LJ	0758M	53CRT	S9184660	261	C					

BLUE FLUORESCENT

57# (84 g/m²) blue matte fluorescent coated paper. Designed for laser, price marking, promotional and general roll label applications. Unique color makes labels stand out. Offers another option when using color coded labels. FSC®-certified paper.

054BZ	00720	40SC	S8122860	242	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
INK JET / LASER										

Recommendations for Storage and Handling of Layflat Label Material

- * Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- * The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- * Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- * Rotate your stock. Use oldest inventory first.
- * Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- * INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

GREEN FLUORESCENT

57# (84 g/m²) green matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

054GZ	0758M	0PBLF	S8189860	262	I					
--------------	-------	-------	-----------------	-----	----------	--	--	--	--	--

ORANGE FLUORESCENT

57# (84 g/m²) orange matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

054OZ	0758M	0PBLF	S8190060	262	I					
--------------	-------	-------	-----------------	-----	----------	--	--	--	--	--

PINK FLUORESCENT

57# (84 g/m²) pink matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

054PZ	0758M	0PBLF	S8190160	262	I					
--------------	-------	-------	-----------------	-----	----------	--	--	--	--	--

RED FLUORESCENT

57# (84 g/m²) red matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

054RZ	0758M	0PBLF	S8190260	262	I					
--------------	-------	-------	-----------------	-----	----------	--	--	--	--	--

YELLOW CHARTREUSE FLUORESCENT

57# (84 g/m²) yellow chartreuse matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

054YZ	0758M	0PBLF	S8189960	262	I					
--------------	-------	-------	-----------------	-----	----------	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
INK JET / LASER										

Recommendations for Storage and Handling of Layflat Label Material

- * Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- * The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- * Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- * Rotate your stock. Use oldest inventory first.
- * Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- * INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

60# MATTE-COATED INK JET

A 60# (88 g/m²) matte-coated, acid-free, inkjet sheet with an exceptionally bright, blue-white shade. It provides high resolution imaging, and excellent smear and water resistance. It is compatible with a broad array of inkjet printers. FSC®-certified.

07INK	00720	40SC	S9206460	246	I					
07INK	00751	40SC	S9205860	249	C					
07INK			S9206260	125	C					

59# GLOSS INKJET PAPER

A 59# (87 g/m²) high gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. Not recommended for flexo printing. FSC®-certified.

1GINK	00720	0PBLF	S8264660	279	C					
1GINK	00720	40SC	S8721460	257	I					
1GINK	00751	40SC	S8714360	258	C					
1GINK	0758M	41LF	S8718860	259	C					

65# SEMI-GLOSS INKJET PAPER

A 65# (97 g/m²) semi gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. FSC®-certified.

SG2NK	0720M	40SC	S9189560	325	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
INK JET / LASER										

Recommendations for Storage and Handling of Layflat Label Material

- * Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- * The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- * Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- * Rotate your stock. Use oldest inventory first.
- * Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- * INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

3.4 MIL MATTE WHITE INK JET BOPP

A 3.4 mil white matte BOPP that is a multi-purpose film for both water-based and pigment ink jet printing. Quick drying on press. The smooth surface allows graphics to really stand out on both black and white, and color printers. Good moisture resistance.

34WIJ	00720	40SC	S9177960	201	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

47# FSC®-CERTIFIED SUPER BRIGHT LASER JET

47# (70 g/m²) Exceptionally bright, uncoated, multi-purpose sheet for laser and ink jet printing. Lighter weight for shipping savings. Thinner caliper for space savings and reduced packaging. Offers the option of more labels on a roll. FSC®-certified.

F47LJ	00757	41LF	S9077660	226	C					
F47LJ	0758M	41LF	S9171560	226	I					
F47LJ	0758M	0PBLF	S9172060	248	I					

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
FILMS: POLYPROPYLENES (CLEAR)										
1.85 MIL CLEAR TOP COATED BOPP										
1.85 mil clear top-coated BOPP is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Ultra clear for a no-label look. Perfect for health and beauty aid, household care, and beverage labeling.										
018CT	00720	40SC	S9064560	178	I	I				
018CT	00751	40SC	S9092760	182	I	I				I
018CT	00960	12NB	S9202560	145	I					I
018CT	00960	40SC	S9213560	181	I					I
018CT	00960	39NK	S9221960	180	I					I
018CT	0720M	40SC	S9090660	181	I					
018CT	0776S	40SC	S9095260	178	C					
018CT	0776S	12NB	S9106460	145	C					
018CT	0976S	40SC	S9213860	176	I					
018CT	0976S	12NB	S9226660	143	I					

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

FILMS: POLYPROPYLENES (CLEAR)

020CL/650SA/12PE

2.0 mil clear top-coated BOPP offers excellent print results with water-based and UV flexo ink systems, and hot stamping. Ultra clear for a no-label look. Perfect for health and beauty aid, household care, pharmaceutical, and beverage labeling. MoistureLock 650 Series is a specially formulated removable adhesive designed for reseal and reclosure applications. Excellent for PET flow wrap and similar substrates. Provides ultra clean removability and a palpable, secure peel. It demonstrates outstanding clarity and resistance to water whitening/blush. Clear 1.2 mil polyester with an excellent surface for die cutting. Great strength for high-speed converting and application.

			SC561600	154						
--	--	--	-----------------	-----	--	--	--	--	--	--

FILMS: POLYPROPYLENES (WHITE)

2.2 MIL FLEXIWHITE™ TC CONFORMABLE BOPP

A 2.2 mil top coated white BOPP offering full wall-to-wall squeeze conformability. Glossy look with a superior print receptive top coating for excellent ink adhesion and print quality. FlexiWhite™ is a Trademark of Green Bay Packaging Inc.

022FW	00751	40SC	S8103360	198	I					
022FW	00751	12NB	S8840360	165	C					

2.3 MIL TOP COATED WHITE BOPP

A 2.3 mil white top coated BOPP, backside coated to aid in adhesive anchorage. Excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.

023WB	00633	12NB	S8167160	170	C					
023WB	0900T	12NB	S9300760	170						
023WB	0900T	92NB	S9300960	155						

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
FILMS: POLYPROPYLENES (WHITE)										

2.3 MIL WHITE TOP COATED BOPP

A 2.3 mil white top coated BOPP with excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.

023WP	00103	40SC	S7000060	202	C					
023WP	00103	12NB	S7895760	169	C					
023WP	00720	40SC	S7630960	200	I					
023WP	00751	40SC	S7722460	204	C					
023WP	00751	12NB	S8823860	171	C					
023WP	00950	40SC	S9221260	202	C	I				I

2.3 MIL WHITE TOP-COATED BOPP

2.3 mil solid white top-coated BOPP. Compatible with UV and water-based flexo, and UV inkjet printing; also hot stamping. Exceptional opacity. Backside treated for adhesive anchorage. Great stiffness for auto application. Ideal for prime labeling.

023WT	00950	40SC	S9221560	202	C		I			
023WT	0720M	40SC	S9133560	203	I					I

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
FILMS: POLYPROPYLENES (WHITE)										

2.4 MIL TOP COATED WHITE LABEL-LYTE™

A 2.4 mil glossy white BOPP top coated for ink adhesion. Has a distinctive pearlescent sheen. Excellent compatibility with UV curing inks and water based flexo ink systems. Label-Lyte is a Trademark of Jindal Films America.

024TL	00720	40SC	S8773560	186	C					
024TL	00751	40SC	S8787060	186	I					
024TL	00751	12NB	S8832660	153	C					
024TL	00950	40SC	S9221060	185	C					
024TL	00950	12NB	S9222260	149	C					

2.6 MIL TOP COATED WHITE LABEL-LYTE™

A 2.6 mil glossy white BOPP top coated for ink adhesion. Has a distinctive pearlescent sheen. Excellent compatibility with UV curing inks and water based flexo ink systems. Label-Lyte is a Trademark of Jindal Films America.

026TL	00720	40SC	S6173060	188	C					
026TL	00747	40SC	S7600560	195	C					
026TL	00751	40SC	S5384060	191	I					
026TL	00950	40SC	S9215460	190	C					
026TL	00950	12NB	S9222160	154	C					
026TL			S6397560	70	C					

3.6 MIL WHITE TC BOPP

A 3.6 mil white BOPP film. UV resistance and top coating suitable for UV screen, UV flexo and waterbased inks. Can be used for window graphics, or other applications where a more substantial film is needed.

036WG	00347	50SC	S6888060	278	I					
036WG	00347	74LF	S9157660	325	I					

Locations:	GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
	WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
				TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
FILMS: POLYPROPYLENES (WHITE)										
2.4 MIL WHITE TOP-COATED BOPP										
2.4 mil white top-coated BOPP. Compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Backside coated for adhesive anchorage. Glossy look. Perfect for prime label applications; health and beauty aid, household care, and beverage labeling.										
24WCB	00950	12NB	S9242860	142	I					I
24WCB	00950	40SC	S9242960	178	I					I
24WCB	0720M	40SC	S9256960	178	I					I
24WCB	0720M	12NB	S9257060	142	I					
24WCB	0976S	40SC	S9273260	173	I					
24WCB	0976S	12NB	S9273360	140	I					

2.4 MIL WHITE TOP-COATED BOPP										
2.4 mil white top-coated BOPP. It is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Glossy look. Perfect for health and beauty aid, household care, and beverage labeling.										
24WCT	00720	40SC	S9134360	178	I					I
24WCT	00751	12NB	S9121060	149	I					
24WCT	00751	40SC	S9123660	182	I					
24WCT	00950	40SC	S9215260	181	I	I	I		I	I
24WCT	00950	12NB	S9221460	144	I					I
24WCT	0720M	40SC	S9119160	181	I					
24WCT	0776S	40SC	S9120460	177	C					I

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
 WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA C - Custom
■ TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
FILMS: POLYPROPYLENES (WHITE)										

2.6 Mil WHITE TOP-COATED BOPP

2.6 mil white top-coated BOPP. Compatible with water-based and UV flexo, and UV inkjet presses. Backside coated for adhesive anchorage. Glossy look. Perfect for prime label applications; health and beauty aid, household care, and beverage labeling.

26WCB	0720M	40SC	S9259160	193	C					
26WCB	0720M	12NB	S9259760	157	I					

2.6 MIL WHITE TOP-COATED BOPP

2.6 mil white top-coated BOPP. It is compatible with water-based and UV flexo, and UV inkjet presses. Glossy look. Perfect for health and beauty aid, household care, and beverage labeling.

26WCT	00103	40SC	S9123160	185	C					
26WCT	00720	40SC	S9121160	183	I					
26WCT	00747	40SC	S9123260	190	C					
26WCT	00751	40SC	S9021560	186	I	I				
26WCT	00950	40SC	S9215360	185	I	I	I			I
26WCT	00950	12NB	S9222360	149	I					
26WCT			S9120660	65	C					

3.4 MIL MATTE WHITE INKJET BOPP

A 3.4 mil white matte BOPP that is a multi-purpose film for both water-based and pigment ink jet printing. Quick drying on press. The smooth surface allows graphics to really stand out on both black and white, and color printers. Good moisture resistance.

34WIJ	00720	40SC	S9177960	201	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations:	GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
	WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
				I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

FILMS: POLYPROPYLENES (WHITE)

023WB/630SA/12PE

A 2.3 mil white top coated BOPP, backside coated to aid in adhesive anchorage. Excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling. MoistureLock 630 Series is a specially formulated removable adhesive designed for reseal and reclosure applications. Excellent for PET flow wrap and similar substrates. Provides ultra clean removability and a smooth, quiet peel. It demonstrates outstanding clarity and resistance to water whitening/blush. Clear 1.2 mil polyester with an excellent surface for die cutting. Great strength for high-speed converting and application.

SC561200	171						
----------	-----	--	--	--	--	--	--

023WB/650SA/12PE

A 2.3 mil white top coated BOPP, backside coated to aid in adhesive anchorage. Excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling. MoistureLock 650 Series is a specially formulated removable adhesive designed for reseal and reclosure applications. Excellent for PET flow wrap and similar substrates. Provides ultra clean removability and a palpable, secure peel. It demonstrates outstanding clarity and resistance to water whitening/blush. Clear 1.2 mil polyester with an excellent surface for die cutting. Great strength for high-speed converting and application.

SC561500	167						
----------	-----	--	--	--	--	--	--

023WT/630SA/12PE

2.3 mil solid white top-coated BOPP. Compatible with UV and water-based flexo, and UV inkjet printing; also hot stamping. Exceptional opacity. Backside treated for adhesive anchorage. Great stiffness for auto application. Ideal for prime labeling. MoistureLock 630 Series is a specially formulated removable adhesive designed for reseal and reclosure applications. Excellent for PET flow wrap and similar substrates. Provides ultra clean removability and a smooth, quiet peel. It demonstrates outstanding clarity and resistance to water whitening/blush. Clear 1.2 mil polyester with an excellent surface for die cutting. Great strength for high-speed converting and application.

SC561400	170						
----------	-----	--	--	--	--	--	--

FILMS: POLYPROPYLENES (VARIABLE IMAGING)

2.9 MIL SYNTHETIC MEDIUM SENSITIVITY FILM

A 2.9 mil BOPP, no phenols added film, with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.

70MKE	00720	40SC	S9272960	196						
70MKE	00751	40SC	S9288560	200						

Locations:	GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
	WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
				TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

FILMS: POLYPROPYLENES (VARIABLE IMAGING)

2.6 MIL THERMAL TRANSFER WHITE LABEL-LYTE™

2.6 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is required. Label-Lyte is a trademark of Jindal Films America.

026TT	00747	40SC	S8773660	192	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

THERMAL TRANSFER WHITE LABEL-LYTE™

White Label-Lyte BOPP with a thermal transfer top coat. Label-Lyte is a Trademark of Jindal Films America.

030TT	00747	40SC	S5213060	199	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

3.0 MIL SYNTHETIC MEDIUM SENSITIVITY FILM

A 3.0 mil BOPP direct thermal film. Medium degree of sensitivity. Top coated for durability. Use when moisture and environmental resistance are important. Dark image for excellent ability to be read and scanned.

070MK	00720	40SC	S4335060	202	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

3.0 MIL TC MATTE WHITE BOPP

A 3.0 mil top coated matte white BOPP. A synthetic paper, it can be used with thermal transfer, flexography, screen, letterpress, and other print

075WP	00747	40SC	S8149152	211	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

TOP COATED KIMDURA® FPG 95

A 4.2 mil (92 g/m²) Kimdura® BOPP specially top coated for thermal transfer, dot matrix, ion deposition and digital printing. Registered Trademark of Neenah Paper, Inc. © 2007 NPI All Rights Reserved.

095TK	00506	40SC	S3252060	256	I					
095TK	00506	50SC	S3256060	272	C					
095TK	00538	50SC	S3286060	272	I					
095TK	00751	50SC	S5391060	273	I					

Locations: GB - Green Bay, WI WIN - Winchester, VA	KC - Kansas City, MO MIN - Minneapolis, MN	ATL - Atlanta, GA LA - Los Angeles, CA	I - Inventory C - Custom TIP Item
---	---	---	---

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

FILMS: POLYPROPYLENES (METALIZED)

1.85 MIL SILVER METALIZED BOPP

1.85 mil clear BOPP metalized on the back for durability. Top coated for print compatibility with water-based and UV flexo, and UV inkjet. Great stiffness for automatic application. Ideal for bright label graphics that will catch the eye of the consumer.

018MT	00720	40SC	S9036760	178	I					
018MT	00751	40SC	S9137460	182	I					I
018MT	00960	12NB	S9210460	145	I					I
018MT	00960	40SC	S9221660	181	I		I			I
018MT	0976S	12NB	S9210860	143	I					
018MT	0976S	40SC	S9240660	176	I					

2.0 MIL SILVER METALIZED BOPP

A 2.0 mil BOPP metalized on the back side for a shiny silver appearance. Top coated for printability with a wide range of ink systems.

021MU	00720	40SC	S8031460	184	I					
021MU	00751	40SC	S7345060	188	C					
021MU	00960	40SC	S9221860	187	C					I

FILMS: POLYSTYRENES

1.5 MIL CLEAR POLYSTYRENE

A 1.5 mil corona treated clear polystyrene. Perfect for use as a base for peel-off coupons and booklets.

015PN	00720	40SC	S8175860	178	C			I		
-------	-------	------	----------	-----	---	--	--	---	--	--

2.0 MIL CLEAR POLYSTYRENE

A 2.0 mil corona treated clear polystyrene. Stiffness allows easy converting and dispensing.

020PN	00103	50SC	S6679060	217	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA
 WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

I - Inventory
 C - Custom
 I - TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

FILMS: POLYSTYRENES

2.5 MIL WHITE POLYSTYRENE

A 2.5 mil matte white polystyrene. Corona treated for excellent ink adhesion. Stiffness allows easy converting and dispensing. Use for primary labels, or as a base for coupons and booklets.

25PSW	00506	40SC	S8263960	231	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

FILMS: POLYESTERS

2 MIL CLEAR TOP COATED POLYESTER

A very clear, top coated polyester film. Top coating allows for printing with most standard flexo and UV letterpress inks.

020MY	00103	50SC	S7855152	242	C					
-------	-------	------	----------	-----	---	--	--	--	--	--

2.0 MIL VALUE WHITE POLYESTER

A matte, white polyester film, top-coated for water-based and U.V. flexographic ink adhesion, and thermal transfer printing. Designed for durable applications – resistant to heat and chemicals. High tear strength.

2VWPT	00406	50SC	S8089560	233	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

FILMS: CLEAR SPECIALTY

2 MIL CLEAR ACETATE

A 2.0 mil clear acetate film with good clarity and printability. It is compostable. Has relatively low tear resistance and is good for tamperproof applications. Meets the ASTM D6400 compost standard.

020AC	00506	50SC	S1106052	234	I					
-------	-------	------	----------	-----	---	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			■ TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
FILMS: WHITE SPECIALTY										

TYVEK®

DuPont™ Tyvek® (1073D) is a 7.5 mil, strong, translucent polyolefin with exceptional strength and moisture resistance. DuPont™ and Tyvek® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.

046TV	00103	40SC	S6881052	227	C					
046TV			S4354052	106	C					

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

HOT MELT PRODUCTS

020CL/630SA/12PE

2.0 mil clear top-coated BOPP offers excellent print results with water-based and UV flexo ink systems, and hot stamping. Ultra clear for a no-label look. Perfect for health and beauty aid, household care, pharmaceutical, and beverage labeling. MoistureLock 630 Series is a specially formulated removable adhesive designed for reseal and reclosure applications. Excellent for PET flow wrap and similar substrates. Provides ultra clean removability and a smooth, quiet peel. It demonstrates outstanding clarity and resistance to water whitening/blush. Clear 1.2 mil polyester with an excellent surface for die cutting. Great strength for high-speed converting and application.

SC561300 158

054SG/767HM/12PE-DES

54# C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. FSC®-certified paper. 767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Clear 1.2 mil polyester liner with an excellent surface for die-cutting. Great strength for high-speed converting and application.

---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

S9230452 199

054SG/767HM/40SC-DES

54# C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. FSC®-certified paper. 767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Liner is a white densified kraft sheet 41# (67 g/m2) with excellent point-to-point caliper control.

---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

S9230352 233

24WCT/767HM/40SC-DES

2.4 mil white top-coated BOPP compatible with water-based, UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. 767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Liner is a white densified kraft sheet 41# (67 g/m2) with excellent point-to-point caliper control.

---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

S9230552 180

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

HOT MELT PRODUCTS

26WCT / 767HM / 12PE

The 2.6 mil glossy white BOPP facer is top coated for dependable ink adhesion. This adhesive has a quick tack and stands up to moisture. Adheres securely to low-energy and textured surfaces. The liner is a 1.2 PET with strength for high-speed converting and application.

S9167360 154 **I**

2WPET / 254HM / 40SC

A 2.0 mil white polyester with our most aggressive hot melt adhesive and a 40# SCK liner. Can be used on a tire sidewall, or other hard-to-stick-to substrates such as rough textures, contaminated surfaces, etc. This polyester face stock has some chemical resistance. This structure has a dry edge for ease of converting and storage.

SC514600 318 **C**

3WBOPP / 254HMHCW / 40SC

3.0 mil white polypropylene combined with our most aggressive hot melt adhesive and a 40# SCK liner. Can be used on a tire sidewall, or other hard-to-stick-to substrates such as rough textures, contaminated surfaces, etc. The facer is thermal transfer printable. This structure has a dry edge for ease of converting and storage.

SC509600 286 **C**

3WBOPP / 298HMHCW / 40SC

A 3.0 mil white polypropylene face stock with an aggressive hot melt adhesive and a 40# SCK liner. The adhesive is approved by the USDA for outdoor markings of monitored crops. Also works well on rough surfaces and low-energy plastics. The facer is thermal transfer printable. This structure has a dry edge for ease of converting and storage.

SC503900 232 **C**

3WBOPP / 298HMHCW / 78LF

A 3.0 mil white polypropylene face stock with an aggressive hot melt adhesive and a 78# liner. the adhesive is approved by the USDA for outdoor markings of monitored crops. Also works well on rough surfaces and low-energy plastics. The facer is thermal transfer printable. This structure has a dry edge for ease of converting and storage.

SC503500 318 **C**

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

HOT MELT PRODUCTS

60ML / 254HMHCW / 40SC

A 60# Matte Litho paper combined with our most aggressive hot melt adhesive and a 40# SCK liner. Can be used on a tire sidewall, or other hard-to-stick-to substrates such as rough textures, contaminated surfaces, etc. This structure has a dry edge for ease of converting and storage

SC514700 338 C [Color Swatches]

60ML / 298HMHCWT / 40SC

A 60# matte litho paper combined with an aggressive hot melt adhesive and a 40# SCK liner. The adhesive is approved by the USDA for outdoor markings of monitored crops. Also works well on rough surfaces and low-energy plastics. This structure has a dry edge for ease of converting and storage.

SC512200 284 C [Color Swatches]

PATTERNED COUPONS

1MBSCPP15PET2UPW102

2-up coupon base with a 1.4 mil PET liner. Adhesive is patterned to create two credit card size coupons across the web. The pattern provides adhesive-free areas along the short edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC510300 162 C [Color Swatches]

1MBSCPP15PET3UPN102

3-up coupon base with a 1.4 mil PET liner. Adhesive is patterned to create three credit card size coupons across the web. The pattern provides adhesive-free areas along the long edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC501300 162 C [Color Swatches]

1MBSCPP15PET4UPN102

4-up coupon base with a 1.4 mil PET liner. Adhesive is patterned to create three credit card size coupons across the web. The pattern provides adhesive-free areas along the long edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC510400 162 C [Color Swatches]

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

PATTERNED COUPONS

1MBSCPP15PET4UPW102

4-up coupon base with a 1.4 mil PET liner. Adhesive is patterned to create four credit card size coupons across the web. The pattern provides adhesive-free areas along the short edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC510200 162 C

1MBSCPP15PET6UPN102

6-up coupon base with a 1.4 mil PET liner. Adhesive is patterned to create three credit card size coupons across the web. The pattern provides adhesive-free areas along the long edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC510100 162 C

1MBSCPP40SC2UPW853

2-up coupon base with a 40# SCK liner. Adhesive is patterned to create two credit card size coupons across the web. The pattern provides adhesive-free areas along the short edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC510800 186 C

1MBSCPP40SC3UPN853

3-up coupon base with a 40# SCK liner. Adhesive is patterned to create three credit card size coupons across the web. The pattern provides adhesive-free areas along the long edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC510900 186 C

1MBSCPP40SC4UPN853

4-up coupon base with a 40# SCK liner. Adhesive is patterned to create three credit card size coupons across the web. The pattern provides adhesive-free areas along the long edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC511000 186 C

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

PATTERNED COUPONS

1MBSCPP40SC4UPW853

4-up coupon base with a 40# SCK liner. Adhesive is patterned to create four credit card size coupons across the web. The pattern provides adhesive-free areas along the short edges, which allow for easy removal by the consumer. Consistent release provides consumer-friendly peel and no pre-dispensing issues.

SC502600	186	C								
----------	-----	---	--	--	--	--	--	--	--	--

1MBSCPP40SCUNIV

Universal coupon base with a 40# SCK liner. Adhesive is diamond-patterned to create a variety of coupon sizes across the web. The patterned breakaway adhesive provides easy removal by the consumer and no pre-dispensing issues. Custom web widths up to 30".

SC502700	186	C								
----------	-----	---	--	--	--	--	--	--	--	--

DURABLE TAGS

TAMPERPROOF ECONOMY

60# white FSC® certified paper laminated on both sides of a 2.0 mil polyester film. This durable material is designed for tags that need to be tear-resistant for security purposes, such as price tags for high-value items.

SC501700	378	C								
----------	-----	---	--	--	--	--	--	--	--	--

INTEGRATED PRODUCTS

30LFL

A 30# layflat liner designed for making integrated labels when the printer applies its own adhesive to the back of the form. Flexo and laser printing compatible. Custom made for the width you need.

SC503700	69	C								
----------	----	---	--	--	--	--	--	--	--	--

40SC / 757 / 41LF

An acrylic adhesive transfer tape product with full adhesive coverage. It functions as a back patch in the creation of integrated labels in forms such as, shipping and return labels for e-commerce, medical forms with patient labels, product tracking in warehouses, and labels included in mailed promotions. Available in 60" masters.

SC515600	215	C								
----------	-----	---	--	--	--	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

INTEGRATED PRODUCTS

40SC / 767HM / 40SC

A hot melt adhesive transfer tape product with a 1/8" dry edge for clean converting. It functions as a back patch in the creation of integrated labels in forms such as, shipping and return labels for e-commerce, medical forms with patient labels, product tracking in warehouses, and labels included in mailed promotions. Custom made for the width you need.

SC509200 229 **C**

BL20CLR4.0

A 2.0 mil clear PET back laminate with 4 inch patterned adhesive - 2.0 mil PET Film / Break Away Coating / 2.0 mil PET Film / 515 Permanent Adhesive / 40# Paper Liner. When the card is removed, a clear window remains.

SC504300 340 **C**

BL20CLR7.75

A 2.0 mil clear PET back laminate with 7.75 inch patterned adhesive - 2.0 mil PET Film / Break Away Coating / 2.0 mil PET Film / 515 Permanent Adhesive / 40# Paper Liner. When the card is removed, a clear window remains.

SC511100 340 **C**

BL20CLRFG

A 2.0 mil clear PET back laminate with full gum adhesive up to 30 inches - 2.0 mil PET Film / Break Away Coating / 2.0 mil PET Film / 515 Permanent Adhesive / 40# Paper Liner. When the card is removed, a clear window remains.

SC504200 340 **C**

BLPAPER4.0

A 40# paper back laminate with 4 inch patterned adhesive - 40# Paper Liner laminated to 1.0 mil Clear PET Film / Break Away Coating / 2.0 mil Clear PET Film / 515 Permanent Adhesive / 40# Paper Liner. When the card is removed, a paper window remains.

SC506000 401 **C**

BLPAPERFG

A 40# paper back laminate with full gum adhesive up to 30 inches - 40# Paper Liner laminated to 1.0 mil Clear PET Film / Break Away Coating / 2.0 mil Clear PET Film / 515 Permanent Adhesive / 40# Paper Liner. When the card is removed, a paper window remains.

SC506100 401 **C**

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

PIGGYBACKS

50# EDP SMUDGE RESISTANT

A 50# (74 g/m²) general purpose uncoated paper. Bright white with excellent smudge resistance. Designed for high performance. FSC®-certified paper.

050ED	0758M 0758M	40SC 40SC	S7725060	356	C					
--------------	----------------	--------------	-----------------	-----	----------	--	--	--	--	--

54# SEMI-GLOSS

54# (78 g/m²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, UV letterpress, and offset methods. FSC®-certified paper.

054SG	0758M 0758M	40SC 50SC	S7686660	379	C					
054SG	0758M 0758M	40SC 40SC	S8027060	361	I					

60# DULL LITHO

60# (89 g/m²) high quality, dull finish litho offering excellent print and die-cut properties. Good for flexographic and offset printing. FSC®-certified paper.

061DL	0758M 0758M	40SC 40SC	S8719060	377	C					
--------------	----------------	--------------	-----------------	-----	----------	--	--	--	--	--

VALUE THERMAL TRANSFER

A 42# (62 g/m²) top-coated, thermal transfer sheet that offers high performance at a lower cost. Strength and opacity are comparable to conventional thermal transfer facers. Exceptional print quality, especially for flood coating. FSC®-certified paper.

VALUT	0758M 0758M	40SC 40SC	S8138960	338	I					
--------------	----------------	--------------	-----------------	-----	----------	--	--	--	--	--

HOT MELT DRY EDGE SOLUTIONS

054SG/767HM/12PE-DES

54# C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. FSC®-certified paper. 767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Clear 1.2 mil polyester liner with an excellent surface for die-cutting. Great strength for high-speed converting and application. ---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

S9230452	199	I					
-----------------	-----	----------	--	--	--	--	--

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			I TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer	Adhesive	Liner	Item	Approx Wgt/ MMSI	GB	WIN	KC	MIN	ATL	LA
-------	----------	-------	------	---------------------	----	-----	----	-----	-----	----

HOT MELT DRY EDGE SOLUTIONS

054SG/767HM/40SC-DES

54# C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. FSC®-certified paper.767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Liner is a white densified kraft sheet 41# (67 g/m2) with excellent point-to-point caliper control. ---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

S9230352 233 I

24WCT/767HM/40SC-DES

2.4 mil white top-coated BOPP compatible with water-based, UV flexo, and UV inkjet presses. Thinner for resource and shipping savings.767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Liner is a white densified kraft sheet 41# (67 g/m2) with excellent point-to-point caliper control. ---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

S9230552 180 I

Locations: GB - Green Bay, WI	KC - Kansas City, MO	ATL - Atlanta, GA	I - Inventory
WIN - Winchester, VA	MIN - Minneapolis, MN	LA - Los Angeles, CA	C - Custom
			TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

CAN'T FIND IT ? CALL 1-800-445-4269



WHITE PAPERS - HIGH-GLOSS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
057HG / 720 / 40SC	57# CAST COATED HI GLOSS 720 ALL TEMP ADHESIVE	S7824560	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
057HG / 751 / 40SC	57# CAST COATED HI GLOSS 751 PERMANENT ADHESIVE (HEAVY CT. WT.)	S8060260	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

WHITE PAPERS - SEMI-GLOSS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
054SG / 278 / 40SC	54# C1S SEMI GLOSS FSC 278 ULTRA REMOVABLE ADH	S8164560	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 633 / 40SC	54# C1S SEMI GLOSS FSC 633 REMOVABLE ADHESIVE	S9175160	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 700 / 40SC	54# C1S SEMI GLOSS FSC 700 PERMANENT ADHESIVE	S7755860	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 720 / 40SC	54# C1S SEMI GLOSS FSC ALL TEMP ADHESIVE	S7724460	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15
054SG / 720M / 092NB	54# C1S SEMI GLOSS FSC 720M ALL TEMP ADHESIVE	S9259860	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 720M / 40SC	54# C1S SEMI GLOSS FSC 720M ALL TEMP ADHESIVE	S8849360	<input checked="" type="checkbox"/> 1.25/ 2.5/ 5/ 10/ 15	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15
054SG / 720M / 12NB	54# C1S SEMI GLOSS FSC 720M ALL TEMP ADHESIVE	S8898960	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
054SG / 747 / 40SC	54# C1S SEMI GLOSS FSC 747 PERMANENT ADHESIVE	S7739560	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 751 / 12NB	54# C1S SEMI GLOSS FSC 751 PERMANENT ADHESIVE	S8823660	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 751 / 40SC	54# C1S SEMI GLOSS FSC 751 PERMANENT ADHESIVE	S7748960	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
054SG / 757 / 0PRLF	54# C1S SEMI GLOSS FSC TACKIFIED PERM ADH	S9234260	<input checked="" type="checkbox"/> [†] 10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 757 / 40SC	54# C1S SEMI GLOSS FSC TACKIFIED PERM ADH	S9022460	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 758M / 41LF	54# C1S SEMI GLOSS FSC 758M PERMANENT ADHESIVE	S9176660	<input checked="" type="checkbox"/> [†] 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 758M / 0PRLF	54# C1S SEMI GLOSS FSC 758M PERMANENT ADHESIVE	S8082660	<input checked="" type="checkbox"/> [†] 10/15	<input checked="" type="checkbox"/> [†] 10/ 15 (exact)	<input checked="" type="checkbox"/> [†] 10/ 15 (exact)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



WHITE PAPERS - SEMI-GLOSS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
054SG / 805 / 0PRLF	54# C1S SEMI GLOSS FSC 805 REMOVABLE ADHESIVE	S8941160	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SG / 80361 / PRLF	54# C1S SEMI GLOSS FSC 80361 REMOVABLE ADHESIVE	S8001560	<input checked="" type="checkbox"/> † 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054SA / 720 / 40SC	054SG OPAQUE FSC ALL TEMP ADHESIVE	S8820660	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
060PR / 272 / 40SC	PREFERRED SEMI GLOSS FSC 272 ULTRA REMOVABLE ADH	S7018060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
060PR / 275 / 41WK	PREFERRED SEMI GLOSS FSC 275 ULTRA REMOVABLE ADH	S9156360	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
060PA / 758M / 40SC	060PR OPAQUE FSC 758M PERMANENT ADHESIVE	S7712860	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
060SG / 720 / 40SC	58# SEMI GLOSS LITHO FSC ALL TEMP ADHESIVE	S7804560	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
060SG / 720 / 12NB	58# SEMI GLOSS LITHO FSC 720 ALL TEMP ADHESIVE	S8210060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 10
060SG / 720M / 40SC	58# SEMI GLOSS LITHO FSC 720M ALL TEMP ADHESIVE	S8899160	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

WHITE PAPERS - MATTE

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
061DL / 720 / 40SC	60# DULL LITHO FSC ALL TEMP ADHESIVE	S4331060	<input checked="" type="checkbox"/>	<input type="checkbox"/>				
061DL / 758M / 40SC	60# DULL LITHO FSC 758M PERMANENT ADHESIVE	S8769360	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

TAG STOCK

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
008GB	8 PT TAG C2S FSC	S7670560	<input checked="" type="checkbox"/>	<input type="checkbox"/>				
008GB / 504 / 40SC	8 PT TAG C2S FSC 504 PERMANENT ADHESIVE	S9941860	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
 All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



EDP									
Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA	
050ED / 720 / 40SC	50# EDP FSC ALL TEMP ADHESIVE	S6069060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
050ED / 720 / 50SC	50# EDP FSC ALL TEMP ADHESIVE	S6499060	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

PHARMACEUTICAL									
Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA	
021RX / 508 / 40SC	3.0 MIL PHARMACY DT FSC 508 PERMANENT ADHESIVE	S9174760	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
021RX / 751 / 40SC	3.0 MIL PHARMACY DT FSC 751 PERMANENT ADHESIVE	S9174660	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20RXE / 508 / 40SC	3.0 MIL PHARMACY DT FSC 508 PERMANENT ADHESIVE	S9263360	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20RXE / 751 / 40SC	3.0 MIL PHARMACY DT FSC 751 PERMANENT ADHESIVE	S9229660	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

FLUORESCENT PAPERS									
Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA	
054GZ / 720 / 40SC	FSC GREEN FLUORESCENT 720 ALL TEMP ADHESIVE	S6231060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054GZ / 720 / 40SC	FSC GREEN FLUORESCENT 720 ALL TEMP ADHESIVE (TIGHT RELEASE)	S7656360	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
054GZ / 758M / 0PBLF	FSC GREEN FLUORESCENT 758M PERMANENT ADHESIVE	S8189860	<input checked="" type="checkbox"/> [†]	<input type="checkbox"/>					
054OZ / 720 / 40SC	FSC ORANGE FLUORESCENT 720 ALL TEMP ADHESIVE	S6235060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054OZ / 720 / 40SC	FSC ORANGE FLUORESCENT 720 ALL TEMP ADHESIVE (TIGHT RELEASE)	S7607960	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
054OZ / 758M / 0PBLF	FSC ORANGE FLUORESCENT 758M PERMANENT ADHESIVE	S8190060	<input checked="" type="checkbox"/> [†]	<input type="checkbox"/>					
054PZ / 720 / 40SC	FSC PINK FLUORESCENT 720 ALL TEMP ADHESIVE	S8034360	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
 All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



FLUORESCENT PAPERS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
054PZ / 720 / 40SC	FSC PINK FLUORESCENT 720 ALL TEMP ADHESIVE (TIGHT RELEASE)	S7748660	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
054PZ / 758M / 0PBLF	FSC PINK FLUORESCENT 758M PERMANENT ADHESIVE	S8190160	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054RZ / 720 / 40SC	FSC RED FLUORESCENT 720 ALL TEMP ADHESIVE	S6066060	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
054RZ / 720 / 40SC	FSC RED FLUORESCENT 720 ALL TEMP ADHESIVE (TIGHT RELEASE)	S7743960	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
054RZ / 758M / 0PBLF	FSC RED FLUORESCENT 758M PERMANENT ADHESIVE	S8190260	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054YZ / 720 / 40SC	FSC YELLOW FLUORESCENT 720 ALL TEMP ADHESIVE	S6237060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
054YZ / 720 / 40SC	FSC YELLOW FLUORESCENT 720 ALL TEMP ADHESIVE (TIGHT RELEASE)	S7748760	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
054YZ / 758M / 0PBLF	FSC YELLOW FLUORESCENT 758M PERMANENT ADHESIVE	S8189960	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

BEER & WINE LABEL

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
061DL / 720 / 40SC	60# DULL LITHO FSC ALL TEMP ADHESIVE	S4331060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
061DL / 758M / 40SC	60# DULL LITHO FSC 758M PERMANENT ADHESIVE	S8769360	<input checked="" type="checkbox"/> 5/ 10/ 15/ 20	<input type="checkbox"/>				
0WEL4 / 747 / 44PM	ESTATELBL#4 WHI LAID FSC 747 PERMANENT ADHESIVE	S8748260	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>				
0WEL8 / 747 / 44PM	FSC ESTATE #8 WH VELLUM 747 PERMANENT ADHESIVE	S8266860	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 2.5/5/10
0WEL9 / 747 / 44PM	ESTATELBL#9 CRM LAID FSC 747 PERMANENT ADHESIVE	S8742160	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 2.5/5/10
0WCSW / 747 / 44PM	FSC CLASSICCRESTSOLAR WH 747 PERMANENT ADHESIVE	S8741852	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>				
70BWF / 747 / 12NB	FSC BRIGHT WHITE FELT WS PERMANENT ADHESIVE	S8903752	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>				
70BWF / 747 / 44PM	FSC BRIGHT WHITE FELT WS 747 PERMANENT ADHESIVE	S8903652	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>				

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



BEER & WINE LABEL

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
KONAL / 720 / 39NK	FSC KONA LIGHT WS 720 ALL TEMP ADHESIVE	S8796760	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>				
PLRNB / 720 / 39NK	FSC ECO WHITE WS 100%PCW 720 ALL TEMP ADHESIVE	S9089960	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
56MSW / 720 / 40SC	SILVER MET PAPER WS 720 ALL TEMP ADHESIVE	S8982560	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

SPECIALTY PAPERS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
060GM / 720 / 40SC	60# NATURAL KRAFT PAPER ALL TEMP ADHESIVE	S8083760	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
060GM / 758M / 40SC	60# NATURAL KRAFT PAPER 758M PERMANENT ADHESIVE	S7649360	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
H2ODP / 611 / 40SC	FSC WATER DISSOLVE PAPER WATER DISSOLVABLE ADH	S8210460	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
KONAL / 720 / 39NK	FSC KONA LIGHT WS 720 ALL TEMP ADHESIVE	S8796760	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

LAMINATED FOILS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
055BG / 720 / 40SC	BRIGHT GOLD LAM FOIL FSC 720 ALL TEMP ADHESIVE	S6301060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
055BS / 720 / 40SC	BRIGHT SLVR LAM FOIL FSC 720 ALL TEMP ADHESIVE	S6299060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
055DG / 720 / 40SC	DULL GOLD LAM FOIL FSC 720 ALL TEMP ADHESIVE	S6300060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
055DS / 720 / 40SC	DULL SILVER LAM FOIL FSC 720 ALL TEMP ADHESIVE	S6306060	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



FOIL SUBSTITUTES

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
018MT / 720 / 40SC	1.85MIL METALIZED TCBOPP ALL TEMP ADHESIVE	S9036760	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
018MT / 751 / 40SC	1.85MIL METALIZED TCBOPP 751 PERMANENT ADHESIVE	S9137460	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
018MT / 960 / 12NB	1.85MIL METALIZED TCBOPP GP FILM ADHESIVE	S9210460	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
018MT / 960 / 40SC	1.85MIL METALIZED TCBOPP GP FILM ADHESIVE	S9221660	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
018MT / 976S / 12NB	1.85MIL METALIZED TCBOPP APR WASHAWAY ALLTEMP ADH	S9210860	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
018MT / 976S / 40SC	1.85MIL METALIZED TCBOPP APR WASHAWAY ALLTEMP ADH	S9240660	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
021MU / 720 / 40SC	2 MIL METALIZED TC BOPP ALL TEMP ADHESIVE	S8031460	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
021MU / 960 / 40SC	2 MIL METALIZED TC BOPP GP FILM ADHESIVE	S9221860	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
057MS / 720 / 40SC	SILVER METALLIZED PAPER 720 ALL TEMP ADHESIVE	S6203060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
56MSW / 720 / 40SC	SILVER MET PAPER WS 720 ALL TEMP ADHESIVE	S8982560	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

THERMAL TRANSFER

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
026TT / 747 / 40SC	2.6 MIL WHITE TT BOPP 747 PERMANENT ADHESIVE	S8773660	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
050HS / 272 / 40SC	HI SPEED THER TRANS FSC 272 ULTRA REMOVABLE ADH	S7019060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
050HS / 275 / 41WK	HI SPEED THER TRANS FSC 275 ULTRA REMOVABLE ADH	S9156260	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
095TK / 538 / 50SC	107 MICRON TC KIMDURA 538 REMOVABLE ADHESIVE	S3286060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
095TK / 751 / 50SC	107 MICRON TC KIMDURA 751 PERMANENT ADHESIVE	S5391060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
0TTFP / 531 / 40SC	SELECT THERMAL TRANS FSC 531 REMOVABLE ADHESIVE	S7843160	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
0TTFP / 720 / 40SC	SELECT THERMAL TRANS FSC ALL TEMP ADHESIVE	S7833160	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
 All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



THERMAL TRANSFER

Table with columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include items like OTTFP / 757 / 40SC, VALUT / 278 / 40SC, etc.

DIRECT THERMAL

Table with columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include items like 021RX / 508 / 40SC, 20RXE / 508 / 40SC, etc.

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto.



DIRECT THERMAL

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
022TD / 720 / 40SC	HI SENSITIVITY DT FSC 720 ALL TEMP ADHESIVE	S6290060	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
015DT / 720 / 40SC	2.3 MIL TC DT FSC 720 ALL TEMP ADHESIVE	S9192179	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
23DTE / 720 / 40SC	TC DIRECT THERMAL FSC 720 ALL TEMP ADHESIVE	S9231660	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24DTE / 633 / 40SC	TC RESISTANT DT FSC 633 REMOVABLE ADHESIVE	S9249760	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24DTE / 720 / 40SC	TC RESISTANT DT FSC 720 ALL TEMP ADHESIVE	S9250760	<input checked="" type="checkbox"/> 5/10/15/ 20	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 10	<input checked="" type="checkbox"/> 5/10/15
25DTE / 720 / 40SC	TC RESISTANT DT FSC 720 ALL TEMP ADHESIVE	S9247160	<input checked="" type="checkbox"/> 2.5/5/10/ 15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15
25DTE / 751 / 40SC	TC RESISTANT DT FSC 751 PERMANENT ADHESIVE	S9254260	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
25DTE / 757 / 40SC	TC RESISTANT DT FSC TACKIFIED PERM ADH	S9254160	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
25NTE / 633 / 40SC	NTC DIRECT THERMAL FSC 633 REMOVABLE ADHESIVE	S9252560	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
25NTE / 720 / 40SC	NTC DIRECT THERMAL FSC 720 ALL TEMP ADHESIVE	S9239960	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15
25NTE / 757 / 40SC	NTC DIRECT THERMAL FSC TACKIFIED PERM ADH	S9247560	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24VTB / 720 / 40SC	VALUE TC DIRECT THER FSC 720 ALL TEMP ADHESIVE	S9030960	<input type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>
070MK / 720 / 40SC	76 MICRON SYN DT ALL TEMP ADHESIVE	S4335060	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
96RKE / 720 / 40SC	4.0 MIL DIR THER BOPP 720 ALL TEMP ADHESIVE	S9271460	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
70MKE / 633 / 40SC	2.9 MIL DT BOPP 633 REMOVABLE ADHESIVE	S9296060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
70MKE / 720 / 40SC	2.9 MIL DT BOPP 720 ALL TEMP ADHESIVE	S9272960	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
70MKE / 751 / 40SC	2.9 MIL DT BOPP 751 PERMANENT ADHESIVE	S9288560	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
22TDE / 720 / 40SC	HIGH SENSITIVITY DT FSC 720 ALL TEMP ADHESIVE	S9289360	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
24VTE / 720 / 40SC	VALUE TC DIRECT THER FSC 720 ALL TEMP ADHESIVE	S9280760	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
 All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



Tailored Inventory Products (T.I.P.)

May



DIRECT THERMAL

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
24VTE / 853 / 40SC	VALUE TC DIRECT THER FSC 853 ALL TEMP ADHESIVE	S9288960	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

DIRECT THERMAL (NO PHENOLS ADDED)

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
021RX / 508 / 40SC	3.0 MIL PHARMACY DT FSC 508 PERMANENT ADHESIVE	S9174760	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
021RX / 751 / 40SC	3.0 MIL PHARMACY DT FSC 751 PERMANENT ADHESIVE	S9174660	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
20RXE / 508 / 40SC	3.0 MIL PHARMACY DT FSC 508 PERMANENT ADHESIVE	S9263360	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
20RXE / 751 / 40SC	3.0 MIL PHARMACY DT FSC 751 PERMANENT ADHESIVE	S9229660	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
23DTE / 720 / 40SC	TC DIRECT THERMAL FSC 720 ALL TEMP ADHESIVE	S9231660	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24DTE / 633 / 40SC	TC RESISTANT DT FSC 633 REMOVABLE ADHESIVE	S9249760	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24DTE / 720 / 40SC	TC RESISTANT DT FSC 720 ALL TEMP ADHESIVE	S9250760	<input checked="" type="checkbox"/> 5/10/15/ 20	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 10	<input checked="" type="checkbox"/> 5/10/15
24VTE / 720 / 40SC	VALUE TC DIRECT THER FSC 720 ALL TEMP ADHESIVE	S9280760	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15
24VTE / 853 / 40SC	VALUE TC DIRECT THER FSC 853 ALL TEMP ADHESIVE	S9288960	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
25DTE / 720 / 40SC	TC RESISTANT DT FSC 720 ALL TEMP ADHESIVE	S9247160	<input checked="" type="checkbox"/> 2.5/ 5/ 10/ 15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15
25DTE / 751 / 40SC	TC RESISTANT DT FSC 751 PERMANENT ADHESIVE	S9254260	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
25DTE / 757 / 40SC	TC RESISTANT DT FSC TACKIFIED PERM ADH	S9254160	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
25NTE / 633 / 40SC	NTC DIRECT THERMAL FSC 633 REMOVABLE ADHESIVE	S9252560	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>				
25NTE / 720 / 40SC	NTC DIRECT THERMAL FSC 720 ALL TEMP ADHESIVE	S9239960	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15
25NTE / 757 / 40SC	NTC DIRECT THERMAL FSC TACKIFIED PERM ADH	S9247560	<input checked="" type="checkbox"/> 5/10/15	<input checked="" type="checkbox"/> 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
70MKE / 633 / 40SC	2.9 MIL DT BOPP 633 REMOVABLE ADHESIVE	S9296060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
 All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

All new structures have a trial period of 6 months. Structures are subject to change without notice.



DIRECT THERMAL (NO PHENOLS ADDED)

Table with 10 columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include 70MKE / 720 / 40SC, 70MKE / 751 / 40SC, 96RKE / 720 / 40SC, and 22TDE / 720 / 40SC.

INK JET / LASER

Table with 10 columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include 050LJ / 720 / 0PBLF, 050LJ / 751 / 0PBLF, 050LJ / 757 / 0PBLF, 050LJ / 758M / 0PBLF, F47LJ / 720 / 40SC, F47LJ / 758M / 41LF, F47LJ / 758M / 0PBLF, 054GZ / 758M / 0PBLF, 054OZ / 758M / 0PBLF, 054PZ / 758M / 0PBLF, 054RZ / 758M / 0PBLF, 054YZ / 758M / 0PBLF, and 1GINK / 720 / 40SC.

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto.



INK JET / LASER

Table with 10 columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include SG2NK / 720M / 40SC, 07INK / 720 / 40SC, 34WIJ / 720 / 40SC, and SGINK / 720 / 40SC.

FILMS: POLYPROPYLENES (CLEAR)

Table with 10 columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include 018CT / 720 / 40SC, 018CT / 720M / 40SC, 018CT / 751 / 40SC, 018CT / 960 / 12NB, 018CT / 960 / 39NK, 018CT / 960 / 40SC, 018CT / 960 / 092NB, 018CT / 976S / 12NB, 018CT / 976S / 40SC, 020CL / 751 / 40SC, 020CL / 960 / 12NB, 020CL / 960 / 40SC, and 036CG / 347 / 50SC.

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



FILMS: POLYPROPYLENES (CLEAR)

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
036CG / 347 / 74LF	3.6 MIL CLEAR TC BOPP GLASS REMOVABLE ADHESIVE	S9127360	<input checked="" type="checkbox"/> †	<input type="checkbox"/>				

FILMS: POLYPROPYLENES (WHITE)

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
023WP / 720 / 40SC	2.3 MIL TC WHITE BOPP ALL TEMP ADHESIVE	S7630960	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
023WP / 950 / 40SC	2.3 MIL TC WHITE BOPP GP FILM ADHESIVE	S9221260	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
023WT / 720M / 40SC	2.3 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE	S9133560	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
023WT / 950 / 40SC	2.3 MIL TC WHITE BOPP GP FILM ADHESIVE	S9221560	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCB / 720M / 40SC	2.4 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE	S9256960	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
24WCB / 720M / 12NB	2.4 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE	S9257060	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCB / 751 / 40SC	2.4 MIL TC WHITE BOPP 751 PERMANENT ADHESIVE	S9258860	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
24WCB / 950 / 40SC	2.4 MIL TC WHITE BOPP GP FILM ADHESIVE	S9242960	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
24WCB / 950 / 12NB	2.4 MIL TC WHITE BOPP GP FILM ADHESIVE	S9242860	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> †
24WCB / 976S / 12NB	2.4 MIL TC WHITE BOPP APR WASHAWAY ALLTEMP ADH	S9273360	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCB / 976S / 40SC	2.4 MIL TC WHITE BOPP APR WASHAWAY ALLTEMP ADH	S9273260	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCT / 720M / 12NB	2.4 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE	S9182460	<input checked="" type="checkbox"/> † 10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCT / 720 / 40SC	2.4 MIL TC WHITE BOPP ALL TEMP ADHESIVE	S9134360	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
24WCT / 720M / 40SC	2.4 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE	S9119160	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCT / 751 / 40SC	2.4 MIL TC WHITE BOPP 751 PERMANENT ADHESIVE	S9123660	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCT / 751 / 12NB	2.4 MIL TC WHITE BOPP 751 PERMANENT ADHESIVE	S9121060	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



FILMS: POLYPROPYLENES (WHITE)

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
24WCT / 776S / 40SC	2.4 MIL TC WHITE BOPP PET RECYCLABLE ADHESIVE	S9120460	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
24WCT / 950 / 12NB	2.4 MIL TC WHITE BOPP GP FILM ADHESIVE	S9221460	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> †
24WCT / 950 / 40SC	2.4 MIL TC WHITE BOPP GP FILM ADHESIVE	S9215260	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
24WCT / 950 / 092NB	2.4 MIL TC WHITE BOPP GP FILM ADHESIVE	S9209960	<input checked="" type="checkbox"/> † 5/10/15	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCT / 976S / 12NB	2.4 MIL TC WHITE BOPP APR WASHAWAY ALLTEMP ADH	S9226060	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24WCT / 976S / 40SC	2.4 MIL TC WHITE BOPP APR WASHAWAY ALLTEMP ADH	S9238560	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
26WCB / 720M / 12NB	2.6 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE	S9259760	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT	2.6 MIL TC WHITE BOPP	S9120660	<input checked="" type="checkbox"/> 5/10/20	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 633 / 40SC	2.6 MIL TC WHITE BOPP 633 REMOVABLE ADHESIVE	S9133660	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 720 / 12NB	2.6 MIL TC WHITE BOPP 720 ALL TEMP ADHESIVE	S9125460	<input checked="" type="checkbox"/> † 10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 720 / 40SC	2.6 MIL TC WHITE BOPP ALL TEMP ADHESIVE	S9121160	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 720M / 40SC	2.6 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE	S9168060	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 751 / 40SC	2.6 MIL TC WHITE BOPP 751 PERMANENT ADHESIVE	S9021560	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 767HM / 12PET	2.6TCWBOPP76712PET	S9167360	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 950 / 12NB	2.6 MIL TC WHITE BOPP GP FILM ADHESIVE	S9222360	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26WCT / 950 / 40SC	2.6 MIL TC WHITE BOPP GP FILM ADHESIVE	S9215360	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
34WIJ / 720 / 40SC	3.4 MIL MATTE WH IJ BOPP 720 ALL TEMP ADHESIVE	S9177960	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
036WG / 347 / 50SC	3.6 ML WHITE TC BOPP GLASS REMOVABLE ADHESIVE	S6888060	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
036WG / 347 / 74LF	3.6 ML WHITE TC BOPP GLASS REMOVABLE ADHESIVE	S9157660	<input checked="" type="checkbox"/> †	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



FILMS: POLYPROPYLENES (VARIABLE IMAGING)

Table with 10 columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include items like 026TT / 747 / 40SC, 070MK / 720 / 40SC, etc.

FILMS: POLYPROPYLENES (METALIZED)

Table with 10 columns: Structure, Description, Item #, GB, WIN, KC, MIN, ATL, LA. Rows include items like 018MT / 720 / 40SC, 018MT / 751 / 40SC, etc.

* Indicates a runnable splice ** Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores



Tailored Inventory Products (T.I.P.)

May



FILMS: POLYSTYRENES

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
015PN / 720 / 40SC	1.5MIL CLEAR POLYSTYRENE 720 ALL TEMP ADHESIVE	S8175860	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

FILMS: POLYESTERS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
2VWPT / 406 / 50SC	2 MIL VALUE WHITE PET TACKIFIED PERM ADHESIVE	S8089560	<input checked="" type="checkbox"/> 2.5/5/10	<input type="checkbox"/>				

PIGGYBACKS

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
054SG / 751 / 12NB / 751 / 40SC	54# C1S SEMI GLOSS FSC 751 PERMANENT ADHESIVE	S9295060	<input checked="" type="checkbox"/>	<input type="checkbox"/>				
054SG / 758M / 40SC / 758M / 40SC	54# C1S SEMI GLOSS FSC 758M PERMANENT ADHESIVE	S8027060	<input checked="" type="checkbox"/>	<input type="checkbox"/>				
VALUT / 757 / 40SC / 757 / 40SC	FSC-VALUE THERMAL TRANS TACKIFIED PERM ADH	S9137960	<input checked="" type="checkbox"/>	<input type="checkbox"/>				
VALUT / 758M / 40SC / 758M / 40SC	FSC-VALUE THERMAL TRANS 758M PERMANENT ADHESIVE	S8138960	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

Other

Structure	Description	Item #	GB	WIN	KC	MIN	ATL	LA
		S8814460	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 10	<input type="checkbox"/>

* Indicates a runnable splice **Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores

- Minimum one slit roll at 3", minimum length varies by product.
- Rolls 5,000' or less are palletized poker chip (stacked on slit edge) with 45 inch maximum height including pallet.
- Rolls 10,000' or greater are palletized on the round (cradle packed).
- All pallets will be stretch wrapped.
- All rolls on 3 inch cores, except as noted.

- Orders placed by 3:00 PM (time zone applicable to location from which shipment originates) will be shipped according to our current lead times.
- Orders placed before cutoff time cannot be changed or canceled after cutoff time.
- No early pickup arrangements, please.

GB=Green Bay, WI WIN=Winchester, VA KC=Kansas City, MO MIN=Minneapolis, MN ATL=Atlanta, GA LA=Los Angeles, CA

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

FAX ORDERS 1-800-705-0111

CAN'T FIND IT? CALL 1-800-445-4269

May 18, 2026

All new structures have a trial period of 6 months. Structures are subject to change without notice.